

Safety Data Sheet

ACRYSEAL HS

Revision date : 2012/06/04

Version: 2.0

Page: 1/6

(30367413/SDS_GEN_CA/EN)

1. Product and Company Identification

Company

BASF Canada Inc.
100 Milverton Drive
Mississauga, ON L5R 4H1, CANADA

24 Hour Emergency Response Information

CANUTEC (reverse charges): (613) 996-6666
BASF HOTLINE: (800) 454-COPE (2673)

2. Hazards Identification

Emergency overview

COMBUSTIBLE.
IRRITANT.
Irritating to eyes and skin.
Contains a carcinogen.

State of matter: liquid
Colour: clear
Odour: solvent-like

Potential health effects**Acute toxicity:**

Vapours may cause drowsiness and dizziness.

Irritation / corrosion:

Irritating to eyes. Repeated exposure may cause skin dryness or cracking.

Sensitization:

There is no evidence of a skin-sensitizing potential.

Potential environmental effects**Aquatic toxicity:**

The product has not been tested.

3. Composition / Information on Ingredients

CAS Number

64742-95-6
108-88-3

Content (W/W)

$\geq 40.0 - \leq 70.0$ %
 $\geq 0.1 - \leq 1.0$ %

Hazardous ingredients

solvent naphtha
Toluene

Safety Data Sheet

ACRYSEAL HS

Revision date : 2012/06/04

Page: 2/6

Version: 2.0

(30367413/SDS_GEN_CA/EN)

53306-54-0

>= 0.0 - <= 3.0 % bis(2-propylheptyl) phthalate

4. First-Aid Measures

General advice:

First aid personnel should pay attention to their own safety. Remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

After contact with skin, wash immediately with plenty of water and soap. Under no circumstances should organic solvent be used. If irritation develops, seek medical attention.

If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

If swallowed:

Rinse mouth immediately and then drink plenty of water, seek medical attention. Do not induce vomiting unless told to by a poison control center or doctor.

Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

5. Fire-Fighting Measures

Flash point: 42.22 °C

Lower explosion limit: 0.9 %(V)

Upper explosion limit: 7 %(V)

Suitable extinguishing media:

foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:

water jet

Hazards during fire-fighting:

carbon monoxide, carbon dioxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

Protective equipment for fire-fighting:

Wear a self-contained breathing apparatus.

Further information:

Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions:

Use personal protective clothing. Do not breathe vapour/aerosol/spray mists. Sources of ignition should be kept well clear. Handle in accordance with good building materials hygiene and safety practice.

Environmental precautions:

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

Safety Data Sheet

ACRYSEAL HS

Revision date : 2012/06/04

Version: 2.0

Page: 3/6

(30367413/SDS_GEN_CA/EN)

Cleanup:

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

7. Handling and Storage

Handling

General advice:

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

Protection against fire and explosion:

Keep away from heat. Prevent electrostatic charge - sources of ignition should be kept well clear - fire extinguishers should be kept handy.

Storage

General advice:

Keep only in the original container in a cool, well-ventilated place. Protect from direct sunlight.

Storage incompatibility:

General advice: Segregate from metals. Segregate from lyes. Segregate from oxidants. Segregate from foods and animal feeds.

Temperature tolerance

Protect from temperatures below: 0 °C

The packed product must be protected from temperatures below the indicated one.

8. Exposure Controls and Personal Protection

Components with workplace control parameters

Toluene	OSHA	TWA value	200 ppm	; CLV	300 ppm	; max. conc.
	ACGIH	500 ppm	; TWA value	20 ppm	;	

Personal protective equipment

Respiratory protection:

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

Hand protection:

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (chemical goggles).

Body protection:

Body protection must be chosen based on level of activity and exposure.

General safety and hygiene measures:

Avoid contact with the skin, eyes and clothing. In order to prevent contamination while handling, closed working clothes and working gloves should be used. Handle in accordance with good building materials hygiene and safety practice. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

Safety Data Sheet

ACRYSEAL HS

Revision date : 2012/06/04
Version: 2.0

Page: 4/6
(30367413/SDS_GEN_CA/EN)

9. Physical and Chemical Properties

Form:	liquid	
Odour:	solvent-like	
Odour threshold:	No data available.	
Colour:	clear	
pH value:		not applicable
Boiling point:	137.22 - 171.11 °C	
Vapour pressure:		The product has not been tested.
Density:	0.9 g/cm3	(20 °C)
Bulk density:		not applicable
Vapour density:		Heavier than air.
Partitioning coefficient n-octanol/water (log Pow):		not applicable
Solubility in water:		slightly soluble
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.	

10. Stability and Reactivity

Substances to avoid:

strong acids, strong bases, strong oxidizing agents

Hazardous reactions:

The product is stable if stored and handled as prescribed/indicated.

Decomposition products:

Thermal decomposition products: carbon oxides

Oxidizing properties:

Based on its structural properties the product is not classified as oxidizing.

11. Toxicological information

Repeated dose toxicity

Information on: bis(2-propylheptyl) phthalate

Assessment of repeated dose toxicity:

Repeated exposure to high doses of the substance causes reversible liver changes in rodents. According to present knowledge, these effects do not occur in man.

Carcinogenicity

Information on: solvent naphtha

The substance caused cancer in animal studies.

Development:

Information on: Toluene

Indications of possible developmental toxicity/teratogenicity were seen in animal studies.

Experiences in humans:

Has degreasing effect on the skin.

Safety Data Sheet

ACRYSEAL HS

Revision date : 2012/06/04
Version: 2.0

Page: 5/6
(30367413/SDS_GEN_CA/EN)

Other Information:

The product has not been tested. The statement has been derived from the properties of the individual components.

12. Ecological Information

Other adverse effects:

Do not allow to enter soil, waterways or waste water channels.

13. Disposal considerations

Waste disposal of substance:

Do not discharge substance/product into sewer system. Dispose of in accordance with local authority regulations.

Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

14. Transport Information

Land transport

TDG

Hazard class:	3
Packing group:	III
ID number:	UN 1993
Hazard label:	3
Proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains NAPHTHA/PETROLEUM, TOLUENE)

Sea transport

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1993
Hazard label:	3
Marine pollutant:	NO
Proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains NAPHTHA/PETROLEUM, TOLUENE)

Air transport

IATA/ICAO

Hazard class:	3
Packing group:	III
ID number:	UN 1993
Hazard label:	3
Proper shipping name:	FLAMMABLE LIQUID, N.O.S. (contains NAPHTHA/PETROLEUM, TOLUENE)

Safety Data Sheet

ACRYSEAL HS

Revision date : 2012/06/04
Version: 2.0

Page: 6/6
(30367413/SDS_GEN_CA/EN)

15. Regulatory Information

Federal Regulations

Registration status:

Chemical DSL, CA released; restriction on use / listed

CEPA, Significant New Activity Restriction (SNAC)

Not for use in products designed to be used by children under the age of 7.
SNAC 12541

WHMIS classification: B3: Combustible Liquid

D2A: Materials Causing Other Toxic Effects - Very toxic material



THIS PRODUCT HAS BEEN CLASSIFIED IN ACCORDANCE WITH THE HAZARD CRITERIA OF THE CPR AND THE MSDS CONTAINS ALL THE INFORMATION REQUIRED BY THE CPR.

16. Other Information

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

MSDS Prepared by:

BASF NA Product Regulations

msds@basf.com

BASF HOTLINE (800) 454 – COPE (2673)

MSDS Prepared on: 2012/06/04

END OF DATA SHEET