

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22

Version: 4.1

Page: 1/13

(30605902/SDS\_GEN\_US/EN)

### 1. Identification

#### Product identifier used on the label

## MasterSeal M 200 flash SLP

#### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

#### Details of the supplier of the safety data sheet

##### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

#### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

#### Other means of identification

Chemical family: No data available.

---

### 2. Hazards Identification

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

#### Classification of the product

Flam. Liq.	3	Flammable liquids
Acute Tox.	3 (Inhalation - vapour)	Acute toxicity
Resp. Sens.	1	Respiratory sensitization
Skin Sens.	1	Skin sensitization
Carc.	2	Carcinogenicity
Repr.	1B (fertility)	Reproductive toxicity
Repr.	1B (unborn child)	Reproductive toxicity
STOT RE	1	Specific target organ toxicity — repeated exposure

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 2/13  
(30605902/SDS\_GEN\_US/EN)

### Label elements

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H226	Flammable liquid and vapour.
H331	Toxic if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H317	May cause an allergic skin reaction.
H351	Suspected of causing cancer.
H372	Causes damage to organs (Central nervous system) through prolonged or repeated exposure.
H360	May damage fertility. May damage the unborn child.

Precautionary Statements (Prevention):

P271	Use only outdoors or in a well-ventilated area.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P260	Do not breathe dust/gas/mist/vapours.
P261	Avoid breathing vapours.
P201	Obtain special instructions before use.
P210	Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P243	Take action to prevent static discharges.
P202	Do not handle until all safety precautions have been read and understood.
P284	In case of inadequate ventilation wear respiratory protection.
P241	Use explosion-proof electrical/ventilating/lighting/equipment.
P264	Wash with plenty of water and soap thoroughly after handling.
P270	Do not eat, drink or smoke when using this product.
P272	Contaminated work clothing should not be allowed out of the workplace.
P242	Use non-sparking tools.
P240	Ground and bond container and receiving equipment.

Precautionary Statements (Response):

P304 + P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.
P311	Call a POISON CENTER or doctor/physician.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower.
P362 + P364	Take off contaminated clothing and wash it before reuse.
P370 + P378	In case of fire: Use alcohol-resistant foam, carbon dioxide, dry powder or water spray for extinction.

Precautionary Statements (Storage):

P403 + P235	Store in a well-ventilated place. Keep cool.
P233	Keep container tightly closed.
P405	Store locked up.

Precautionary Statements (Disposal):

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 3/13  
(30605902/SDS\_GEN\_US/EN)

P501 Dispose of contents/container to hazardous or special waste collection point.

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

#### Labeling of special preparations (GHS):

CONTAINS ISOCYANATES. INHALATION OF ISOCYANATE MISTS OR VAPORS MAY CAUSE RESPIRATORY IRRITATION, BREATHLESSNESS, CHEST DISCOMFORT AND REDUCED PULMONARY FUNCTION. OVEREXPOSURE WELL ABOVE THE PEL MAY RESULT IN BRONCHITIS, BRONCHIAL SPASMS AND PULMONARY EDEMA. LONG-TERM EXPOSURE TO ISOCYANATES HAS BEEN REPORTED TO CAUSE LUNG DAMAGE, INCLUDING REDUCED LUNG FUNCTION WHICH MAY BE PERMANENT. ACUTE OR CHRONIC OVEREXPOSURE TO ISOCYANATES MAY CAUSE SENSITIZATION IN SOME INDIVIDUALS, RESULTING IN ALLERGIC RESPIRATORY REACTIONS INCLUDING WHEEZING, SHORTNESS OF BREATH AND DIFFICULTY BREATHING. ANIMAL TESTS INDICATE THAT SKIN CONTACT MAY PLAY A ROLE IN CAUSING RESPIRATORY SENSITIZATION.

### 3. Composition / Information on Ingredients

#### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

<u>CAS Number</u>	<u>Weight %</u>	<u>Chemical name</u>
1317-65-3	>= 0.0 - < 50.0%	Limestone
14807-96-6	>= 10.0 - < 15.0%	talc
8052-41-3	>= 3.0 - < 5.0%	Stoddard solvent
584-84-9	>= 3.0 - < 5.0%	toluene-2,4-diisocyanate
7778-18-9	>= 0.0 - < 5.0%	Calcium sulphate
13463-67-7	>= 0.0 - < 3.0%	Titanium dioxide
2530-83-8	>= 0.3 - < 1.0%	trimethoxy(3-(oxiranylmethoxy)propyl)silane
91-08-7	>= 0.3 - < 1.0%	toluene-2,6-diisocyanate
77-58-7	>= 0.1 - < 0.2%	dibutyltin dilaurate

### 4. First-Aid Measures

#### Description of first aid measures

##### General advice:

First aid personnel should pay attention to their own safety. Immediately remove contaminated clothing.

##### If inhaled:

Remove the affected individual into fresh air and keep the person calm. Assist in breathing if necessary. Immediate medical attention required.

##### If on skin:

Wash affected areas thoroughly with soap and water. If irritation develops, seek medical attention.

##### If in eyes:

In case of contact with the eyes, rinse immediately for at least 15 minutes with plenty of water. Immediate medical attention required.

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 4/13  
(30605902/SDS\_GEN\_US/EN)

### **If swallowed:**

Rinse mouth and then drink plenty of water. Do not induce vomiting. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions. Immediate medical attention required.

### **Most important symptoms and effects, both acute and delayed**

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Eye irritation, skin irritation, allergic symptoms

Hazards: Respiratory sensitization may result in allergic (asthma-like) signs in the lower respiratory tract including wheezing, shortness of breath and difficulty breathing, the onset of which may be delayed. Repeated inhalation of high concentrations may cause lung damage, including reduced lung function, which may be permanent. Substances eliciting lower respiratory tract irritation may worsen the asthma-like reactions that may be produced by product exposures.

### **Indication of any immediate medical attention and special treatment needed**

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## **5. Fire-Fighting Measures**

### **Extinguishing media**

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

### **Special hazards arising from the substance or mixture**

Hazards during fire-fighting:  
nitrous gases, fumes/smoke, isocyanate, vapour

### **Advice for fire-fighters**

Protective equipment for fire-fighting:  
Firefighters should be equipped with self-contained breathing apparatus and turn-out gear.

### **Further information:**

Keep containers cool by spraying with water if exposed to fire. Dispose of fire debris and contaminated extinguishing water in accordance with official regulations.

---

## **6. Accidental release measures**

### **Personal precautions, protective equipment and emergency procedures**

Clear area. Ensure adequate ventilation. Wear suitable personal protective clothing and equipment.

### **Environmental precautions**

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 5/13  
(30605902/SDS\_GEN\_US/EN)

### Methods and material for containment and cleaning up

For small amounts: Absorb isocyanate with suitable absorbent material (see § 40 CFR, sections 260, 264 and 265 for further information). Shovel into open container. Do not make container pressure tight. Move container to a well-ventilated area (outside). Spill area can be decontaminated with the following recommended decontamination solution: Mixture of 90 % water, 8 % concentrated ammonia, 2 % detergent. Add at a 10 to 1 ratio. Allow to stand for at least 48 hours to allow escape of evolved carbon dioxide.

For large amounts: If temporary control of isocyanate vapor is required, a blanket of protein foam or other suitable foam (available from most fire departments) may be placed over the spill. Transfer as much liquid as possible via pump or vacuum device into closed but not sealed containers for disposal.

For residues: The following measures should be taken for final cleanup: Wash down spill area with decontamination solution. Allow solution to stand for at least 10 minutes.  
Dike spillage.

---

## 7. Handling and Storage

### Precautions for safe handling

Provide suitable exhaust ventilation at the processing machines. Ensure thorough ventilation of stores and work areas. Avoid aerosol formation. When handling heated product, vapours of the product should be ventilated, and respiratory protection used. Wear respiratory protection when spraying. Danger of bursting when sealed gastight. Protect against moisture. If bulging of drum occurs, transfer to well ventilated area, puncture to relieve pressure, open vent and let stand for 48 hours before resealing.

### Conditions for safe storage, including any incompatibilities

No applicable information available.

Suitable materials for containers: tinned carbon steel (Tinplate)

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

---

## 8. Exposure Controls/Personal Protection

### Components with occupational exposure limits

dibutyltin dilaurate	OSHA PEL	PEL 0.1 mg/m <sup>3</sup> (tin (Sn)); TWA value 0.1 mg/m <sup>3</sup> (tin (Sn)); SKIN_FINAL (tin (Sn)); The substance can be absorbed through the skin.
	ACGIH TLV	TWA value 0.1 mg/m <sup>3</sup> (tin (Sn)); STEL value 0.2 mg/m <sup>3</sup> (tin (Sn)); Skin Designation (tin (Sn)); The substance can be absorbed through the skin.
toluene-2,6-diisocyanate	ACGIH TLV	TWA value 0.005 ppm ; STEL value 0.02 ppm ;
toluene-2,4-diisocyanate	OSHA PEL	CLV 0.02 ppm 0.14 mg/m <sup>3</sup> ; TWA value 0.005 ppm 0.04 mg/m <sup>3</sup> ; STEL value 0.02 ppm 0.15 mg/m <sup>3</sup> ;
	ACGIH TLV	TWA value 0.005 ppm ; STEL value 0.02 ppm ;

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 6/13  
(30605902/SDS\_GEN\_US/EN)

Limestone	OSHA PEL	PEL 5 mg/m3 Respirable fraction ; PEL 15 mg/m3 Total dust ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
Calcium sulphate	OSHA PEL	PEL 15 mg/m3 Total dust ; PEL 5 mg/m3 Respirable fraction ; TWA value 15 mg/m3 Total dust ; TWA value 5 mg/m3 Respirable fraction ;
	ACGIH TLV	TWA value 10 mg/m3 Inhalable fraction ;
Titanium dioxide	OSHA PEL	PEL 15 mg/m3 Total dust ; TWA value 10 mg/m3 Total dust ;
	ACGIH TLV	TWA value 10 mg/m3 ;
talc	OSHA PEL	TWA value 2 mg/m3 Respirable dust ; TWA value 20 millions of particles per cubic foot of air ; TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 0.1 mg/m3 Respirable ; The exposure limit is calculated from the equation, $10mg/m^3/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 0.3 mg/m3 Total dust ; The exposure limit is calculated from the equation, $30mg/m^3/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.
	ACGIH TLV	TWA value 2 mg/m3 Respirable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.
Silica	OSHA PEL	TWA value 20 millions of particles per cubic foot of air ; TWA value 0.8 mg/m3 ; The exposure limit is calculated from the equation, $80mg/m^3/(\%SiO_2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.
Stoddard solvent	OSHA PEL	PEL 500 ppm 2,900 mg/m3 ; PEL 500 ppm 2,900 mg/m3 ; TWA value 100 ppm 525 mg/m3 ; TWA value 100 ppm 525 mg/m3 ;
	ACGIH TLV	TWA value 100 ppm ; TWA value 100 ppm ;

### Advice on system design:

Provide adequate exhaust ventilation to control work place concentrations.

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 7/13  
(30605902/SDS\_GEN\_US/EN)

### Personal protective equipment

#### **Respiratory protection:**

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators. When atmospheric levels may exceed the occupational exposure limit (PEL or TLV) NIOSH-certified air-purifying respirators equipped with an organic vapor sorbent and particulate filter can be used as long as appropriate precautions and change out schedules are in place. For emergency or non-routine, high exposure situations, including confined space entry, use a NIOSH-certified full facepiece pressure demand self-contained breathing apparatus (SCBA) or a full facepiece pressure demand supplied-air respirator (SAR) with escape provisions.

#### **Hand protection:**

Chemical resistant protective gloves should be worn to prevent all skin contact., Suitable materials may include, chloroprene rubber (Neoprene), nitrile rubber (Buna N), chlorinated polyethylene, polyvinylchloride (Pylox), butyl rubber, fluoroelastomer (Viton), depending upon conditions of use.

#### **Eye protection:**

Tightly fitting safety goggles (chemical goggles). Wear face shield if splashing hazard exists.

#### **Body protection:**

Cover as much of the exposed skin as possible to prevent all skin contact., Suitable materials may include, saran-coated material, depending upon conditions of use.

#### **General safety and hygiene measures:**

Wear protective clothing as necessary to prevent contact. Eye wash fountains and safety showers must be easily accessible. Observe the appropriate PEL or TLV value. Wash soiled clothing immediately. Remove contaminated clothing immediately and clean before re-use or dispose if necessary.

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	solvent-like	
Odour threshold:	No applicable information available.	
Colour:	off-white	
pH value:	neutral to slightly alkaline	
Melting point:	No applicable information available.	
Boiling point:	179 °C	(estimated)
Sublimation point:	No applicable information available.	
Flash point:	43.33 °C	(ASTM D3278)
Flammability:	not determined	
Lower explosion limit:	1.0 %(V)	
Upper explosion limit:	7.0 %(V)	
Vapour pressure:	The product has not been tested.	
Density:	9.6807 lb/USg ( 20 °C) 1.1600 g/cm <sup>3</sup> ( 20 °C)	
Relative density:	1.16	
Bulk density:	not applicable	
Vapour density:	Heavier than air.	
Partitioning coefficient n-octanol/water (log Pow):	No data available.	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Viscosity, dynamic:	No applicable information available.	
Solubility in water:	slightly soluble	
Solubility (quantitative):	No applicable information available.	

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22

Version: 4.1

Page: 8/13

(30605902/SDS\_GEN\_US/EN)

---

Solubility (qualitative):	No applicable information available.
Evaporation rate:	No applicable information available.
Other Information:	If necessary, information on other physical and chemical parameters is indicated in this section.

---

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

#### Conditions to avoid

See MSDS section 7 - Handling and storage.

#### Incompatible materials

strong acids, strong bases, strong oxidizing agents, strong reducing agents

#### Hazardous decomposition products

Decomposition products:

No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

No decomposition if stored and handled as prescribed/indicated.

---

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Toxic by inhalation.

##### Oral

No data available.

##### Inhalation

Type of value: ATE

Value: 2.15 mg/l

Determined for vapor

##### Dermal

No data available.

##### Assessment other acute effects

No applicable information available.



# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 9/13  
(30605902/SDS\_GEN\_US/EN)

### Irritation / corrosion

Assessment of irritating effects: Not irritating to eyes and skin. The product has not been tested. The statement has been derived from the properties of the individual components.

### Sensitization

Assessment of sensitization: Sensitization after skin contact possible. The substance may cause sensitization of the respiratory tract. As a result of previous repeated overexposures or a single large dose, certain individuals will develop isocyanate sensitization (chemical asthma) which will cause them to react to a later exposure to isocyanate at levels well below the PEL/TLV. These symptoms, which include chest tightness, wheezing, cough, shortness of breath, or asthmatic attack, could be immediate or delayed up to several hours after exposure. Similar to many non-specific asthmatic responses, there are reports that once sensitized an individual can experience these symptoms upon exposure to dust, cold air, or other irritants. This increased lung sensitivity can persist for weeks and in severe cases for several years. Chronic overexposure to isocyanates has also been reported to cause lung damage, including a decrease in lung function, which may be permanent. Prolonged contact can cause reddening, swelling, rash, scaling, or blistering. In those who have developed a skin sensitization, these symptoms can develop as a result of contact with very small amounts of liquid material, or even as a result of vapour-only exposure. Animal tests indicate that skin contact may play a role in causing respiratory sensitization.

*Information on: toluene-2,4-diisocyanate*

*Assessment of sensitization:*

*The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.*

*Information on: toluene-2,6-diisocyanate*

*Assessment of sensitization:*

*The substance may cause sensitization of the respiratory tract. Sensitization after skin contact possible.*

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: May cause central nervous system effects. The product has not been tested. The statement has been derived from the properties of the individual components.

*Information on: toluene-2,4-diisocyanate*

*Assessment of repeated dose toxicity: The substance may cause damage to the lung even after repeated inhalation of low doses, as shown in animal studies.*

*Information on: toluene-2,6-diisocyanate*

*Assessment of repeated dose toxicity: The substance may cause damage to the lung even after repeated inhalation of low doses, as shown in animal studies. The product has not been tested. A mixture of isomers has been tested.*

### Genetic toxicity

Assessment of mutagenicity: The substance was mutagenic in various bacterial test systems; however, a mutagenic effect could not be confirmed in mammalian cell culture.

### Carcinogenicity

Assessment of carcinogenicity: Contains a compound classified as IARC Group 2B (possibly carcinogenic to humans).

*Information on: toluene-2,6-diisocyanate*

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 10/13  
(30605902/SDS\_GEN\_US/EN)

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans).*

*Information on: toluene-2,4-diisocyanate*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). NTP listed carcinogen*

*Information on: Titanium dioxide*

*Assessment of carcinogenicity: IARC (International Agency for Research on Cancer) has classified this substance as group 2B (The agent is possibly carcinogenic to humans). In long-term studies in rats in which the substance was given by inhalation, a carcinogenic effect was observed. Tumors were only observed in rats after chronic inhalative exposure to high concentrations which caused sustained lung inflammation. In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. Dermal exposure is not expected to be carcinogenic.*

-----

### Reproductive toxicity

Assessment of reproduction toxicity: Contains a reproductive toxin.

*Information on: dibutyltin dilaurate*

-----

### Teratogenicity

Assessment of teratogenicity: Contains a suspect teratogen.

### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

## Symptoms of Exposure

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11., Eye irritation, skin irritation, allergic symptoms

### Medical conditions aggravated by overexposure

The isocyanate component is a respiratory sensitizer. It may cause allergic reaction leading to asthma-like spasms of the bronchial tubes and difficulty in breathing. Medical supervision of all employees who handle or come into contact with isocyanates is recommended. Contact may aggravate pulmonary disorders. Persons with history of respiratory disease or hypersensitivity should not be exposed to this product. Preemployment and periodic medical examinations with respiratory function tests (FEV, FVC as a minimum) are suggested. Persons with asthmatic conditions, chronic bronchitis, other chronic respiratory diseases, recurrent eczema or pulmonary sensitization should be excluded from working with isocyanates. Once a person is diagnosed as having pulmonary sensitization (allergic asthma) to isocyanates, further exposure is not recommended.

---

## 12. Ecological Information

### Toxicity

Aquatic toxicity

Assessment of aquatic toxicity:

Based on available Data, the classification criteria are not met.

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 11/13  
(30605902/SDS\_GEN\_US/EN)

### Persistence and degradability

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

Poorly biodegradable.

The product is unstable in water. The elimination data also refer to products of hydrolysis.

#### Assessment biodegradation and elimination (H<sub>2</sub>O)

*Information on: TDI*

*Poorly biodegradable. The product is unstable in water. The elimination data also refer to products of hydrolysis.*

### Mobility in soil

#### Assessment transport between environmental compartments

Adsorption to solid soil phase is not expected.

### Additional information

Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## 13. Disposal considerations

### **Waste disposal of substance:**

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### **Container disposal:**

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

## 14. Transport Information

### **Land transport**

USDOT

Hazard class:	C
Packing group:	III
ID number:	UN 1263
Hazard label:	CBL
Proper shipping name:	PAINT, COMBUSTIBLE LIQUID

Classified as combustible liquid in containers greater than 119 gallons.

### **Sea transport**

IMDG

Hazard class:	3
Packing group:	III
ID number:	UN 1263
Hazard label:	3

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 12/13  
(30605902/SDS\_GEN\_US/EN)

Marine pollutant: NO  
Proper shipping name: PAINT

### Air transport

IATA/ICAO

Hazard class: 3  
Packing group: III  
ID number: UN 1263  
Hazard label: 3  
Proper shipping name: PAINT

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical TSCA, US released / listed

TSCA § 5(a) proposed Significant New Use Restriction (SNUR)  
This product contains a substance subject to a pending SNUR.  
40 CFR 721.10789

**EPCRA 311/312 (Hazard categories):** Acute; Chronic; Fire

#### EPCRA 313:

<u>CAS Number</u>	<u>Chemical name</u>
91-08-7	toluene-2,6-diisocyanate
584-84-9	toluene-2,4-diisocyanate

#### CERCLA RQ

<u>CAS Number</u>	<u>Chemical name</u>
100 LBS	584-84-9; 91-08-7 toluene-2,4-diisocyanate; toluene-2,6-diisocyanate

### State regulations

#### State RTK

	<u>CAS Number</u>	<u>Chemical name</u>
NJ	584-84-9	toluene-2,4-diisocyanate
	1317-65-3	Limestone
	7778-18-9	Calcium sulphate
	13463-67-7	Titanium dioxide
	14807-96-6	talc
	8052-41-3	Stoddard solvent
	91-08-7	toluene-2,6-diisocyanate
PA	14808-60-7	crystalline silica
	584-84-9	toluene-2,4-diisocyanate
	1317-65-3	Limestone
	7778-18-9	Calcium sulphate
	13463-67-7	Titanium dioxide
	14807-96-6	talc
	112945-52-5	Silica
	8052-41-3	Stoddard solvent

#### CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

# Safety Data Sheet

## MasterSeal M 200 flash SLP

Revision date : 2017/05/22  
Version: 4.1

Page: 13/13  
(30605902/SDS\_GEN\_US/EN)

---

**NFPA Hazard codes:**

Health : 3      Fire: 2      Reactivity: 0      Special:

---

### 16. Other Information

**SDS Prepared by:**

BASF NA Product Regulations

SDS Prepared on: 2017/05/22

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET