

## Safety Data Sheet

### MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27

Version: 1.0

Page: 1/10

(30367671/SDS\_GEN\_US/EN)

#### 1. Identification

##### Product identifier used on the label

### MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

##### Recommended use of the chemical and restriction on use

Recommended use\*: for industrial and professional users

\* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

##### Details of the supplier of the safety data sheet

###### Company:

BASF CORPORATION  
100 Park Avenue  
Florham Park, NJ 07932, USA

Telephone: +1 973 245-6000

##### Emergency telephone number

CHEMTREC: 1-800-424-9300  
BASF HOTLINE: 1-800-832-HELP (4357)

##### Other means of identification

Synonyms: Not Available

---

#### 2. Hazards Identification

##### According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

##### Classification of the product

Eye Dam./Irrit.	2A	Serious eye damage/eye irritation
STOT RE	1 (by inhalation)	Specific target organ toxicity — repeated exposure

##### Label elements

# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27  
Version: 1.0

Page: 2/10  
(30367671/SDS\_GEN\_US/EN)

Pictogram:



Signal Word:  
Danger

Hazard Statement:

H319 Causes serious eye irritation.  
H372 Causes damage to organs (Lung) through prolonged or repeated exposure (inhalation).

Precautionary Statements (Prevention):

P280 Wear eye/face protection.  
P260 Do not breathe dust/gas/mist/vapours.  
P270 Do not eat, drink or smoke when using this product.  
P264 Wash with plenty of water and soap thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
P337 + P311 If eye irritation persists: Call a POISON CENTER or doctor/physician.

Precautionary Statements (Disposal):

P501 Dispose of contents/container to hazardous or special waste collection point.

### Hazards not otherwise classified

If applicable information is provided in this section on other hazards which do not result in classification but which may contribute to the overall hazards of the substance or mixture.

---

## 3. Composition / Information on Ingredients

**According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200**

<u>CAS Number</u>	<u>Content (W/W)</u>	<u>Chemical name</u>
14808-60-7	>= 25.0 - < 50.0 %	crystalline silica
7727-43-7	>= 15.0 - < 20.0 %	Barium sulfate
1344-28-1	>= 0.1 - < 3.0 %	Aluminum oxide
64742-95-6	>= 0.3 - < 1.0 %	solvent naphtha
12136-45-7	>= 0.0 - < 1.0 %	dipotassium oxide
4169-04-4	>= 0.2 - < 1.0 %	2-phenoxypropanol
1313-59-3	>= 0.0 - < 1.0 %	disodium oxide
1305-78-8	>= 0.0 - < 0.2 %	calcium oxide

---

## 4. First-Aid Measures

Description of first aid measures

# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27

Page: 3/10

Version: 1.0

(30367671/SDS\_GEN\_US/EN)

### General advice:

First aid personnel should pay attention to their own safety. If the patient is likely to become unconscious, place and transport in stable sideways position (recovery position). Immediately remove contaminated clothing.

### If inhaled:

Keep patient calm, remove to fresh air, seek medical attention.

### If on skin:

Immediately wash thoroughly with soap and water, seek medical attention.

### If in eyes:

Wash affected eyes for at least 15 minutes under running water with eyelids held open, consult an eye specialist.

### If swallowed:

Immediately rinse mouth and then drink 200-300 ml of water, seek medical attention.

### Most important symptoms and effects, both acute and delayed

Symptoms: The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

### Indication of any immediate medical attention and special treatment needed

#### Note to physician

Treatment: Treat according to symptoms (decontamination, vital functions), no known specific antidote.

---

## 5. Fire-Fighting Measures

### Extinguishing media

Suitable extinguishing media:  
foam, water spray, dry powder, carbon dioxide

Unsuitable extinguishing media for safety reasons:  
water jet

### Special hazards arising from the substance or mixture

Hazards during fire-fighting:  
carbon dioxide, carbon monoxide, harmful vapours, nitrogen oxides, fumes/smoke, carbon black

### Advice for fire-fighters

Protective equipment for fire-fighting:  
Wear a self-contained breathing apparatus.

### Further information:

The degree of risk is governed by the burning substance and the fire conditions. If exposed to fire, keep containers cool by spraying with water. Collect contaminated extinguishing water separately, do not allow to reach sewage or effluent systems. Contaminated extinguishing water must be disposed of in accordance with official regulations.

# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27  
Version: 1.0

Page: 4/10  
(30367671/SDS\_GEN\_US/EN)

### 6. Accidental release measures

#### Personal precautions, protective equipment and emergency procedures

Do not breathe vapour/aerosol/spray mists. Wear eye/face protection. If exposed to high vapour concentration, leave area immediately. Use personal protective clothing. Handle in accordance with good building materials hygiene and safety practice.

#### Environmental precautions

Contain contaminated water/firefighting water. Do not discharge into drains/surface waters/groundwater.

#### Methods and material for containment and cleaning up

For small amounts: Pick up with inert absorbent material (e.g. sand, earth etc.). Dispose of contaminated material as prescribed.

For large amounts: Pump off product.

### 7. Handling and Storage

#### Precautions for safe handling

Avoid aerosol formation. Avoid inhalation of mists/vapours. Avoid skin contact. No special measures necessary provided product is used correctly.

#### Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Keep only in the original container in a cool, dry, well-ventilated place away from ignition sources, heat or flame. Protect from direct sunlight.

### 8. Exposure Controls/Personal Protection

#### Components with occupational exposure limits

calcium oxide	OSHA PEL ACGIH TLV	PEL 5 mg/m <sup>3</sup> ; TWA value 5 mg/m <sup>3</sup> ; TWA value 2 mg/m <sup>3</sup> ;
Aluminum oxide	OSHA PEL ACGIH TLV	PEL 5 mg/m <sup>3</sup> Respirable fraction ; PEL 15 mg/m <sup>3</sup> Total dust ; TWA value 10 mg/m <sup>3</sup> Total dust ; TWA value 5 mg/m <sup>3</sup> Respirable fraction ; TWA value 1 mg/m <sup>3</sup> Respirable fraction ;
Barium sulfate	OSHA PEL ACGIH TLV	PEL 5 mg/m <sup>3</sup> Respirable fraction ; PEL 15 mg/m <sup>3</sup> Total dust ; TWA value 10 mg/m <sup>3</sup> Total dust ; TWA value 5 mg/m <sup>3</sup> Respirable fraction ; TWA value 10 mg/m <sup>3</sup> ; The value is for particulate matter containing no asbestos and <1% crystalline silica. TWA value 5 mg/m <sup>3</sup> Inhalable fraction ; The value is for particulate matter containing no asbestos and <1% crystalline silica.

# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27  
Version: 1.0

Page: 5/10  
(30367671/SDS\_GEN\_US/EN)

crystalline silica	OSHA PEL	TWA value 2.4 millions of particles per cubic foot of air Respirable ; The exposure limit is calculated from the equation, $250/(\%SiO_2+5)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 0.1 mg/m <sup>3</sup> Respirable ; The exposure limit is calculated from the equation, $10/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits. TWA value 0.3 mg/m <sup>3</sup> Total dust ; The exposure limit is calculated from the equation, $30/(\%SiO_2+2)$ , using a value of 100% SiO <sub>2</sub> . Lower percentages of SiO <sub>2</sub> will yield higher exposure limits.
	ACGIH TLV	TWA value 0.025 mg/m <sup>3</sup> Respirable fraction ;

### Personal protective equipment

#### **Respiratory protection:**

When workers are facing concentrations above the occupational exposure limits they must use appropriate certified respirators.

#### **Hand protection:**

Wear chemical resistant protective gloves., Manufacturer's directions for use should be observed because of great diversity of types.

#### **Eye protection:**

Tightly fitting safety goggles (chemical goggles).

#### **Body protection:**

Body protection must be chosen based on level of activity and exposure.

#### **General safety and hygiene measures:**

Do not inhale gases/vapours/aerosols. Avoid contact with the skin, eyes and clothing. Avoid exposure - obtain special instructions before use. Handle in accordance with good building materials hygiene and safety practice. Wearing of closed work clothing is recommended. When using, do not eat, drink or smoke. Hands and/or face should be washed before breaks and at the end of the shift. At the end of the shift the skin should be cleaned and skin-care agents applied. Gloves must be inspected regularly and prior to each use. Replace if necessary (e.g. pinhole leaks).

---

## 9. Physical and Chemical Properties

Form:	liquid	
Odour:	faint odour	
Odour threshold:		No applicable information available.
Colour:	various	
pH value:		neutral to slightly alkaline
Boiling point:	140.00 - 242.78 °C	
Flash point:	93.34 °C > 201 °F	(ASTM D56, closed cup) (ASTM D56, closed cup)

# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27  
Version: 1.0

Page: 6/10  
(30367671/SDS\_GEN\_US/EN)

Flammability:	not determined	
Lower explosion limit:	0.7 %(V)	
Upper explosion limit:	9.4 %(V)	
Density:	approx. 1.63	( 20 °C)
	g/cm3	
	13.35 - 13.85	( 73 °F)
	lb/USg	
Vapour density:	Heavier than air.	
Thermal decomposition:	No decomposition if stored and handled as prescribed/indicated.	
Solubility in water:	( 15 °C) not soluble	

### 10. Stability and Reactivity

#### Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:  
Not an oxidizer.

#### Chemical stability

The product is stable if stored and handled as prescribed/indicated.

#### Possibility of hazardous reactions

The product is stable if stored and handled as prescribed/indicated.

#### Conditions to avoid

See MSDS section 7 - Handling and storage.

#### Incompatible materials

strong oxidizing agents, strong bases, strong acids

#### Hazardous decomposition products

Decomposition products:  
No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:  
No decomposition if stored and handled as prescribed/indicated.

### 11. Toxicological information

#### Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

#### Acute Toxicity/Effects

##### Acute toxicity

Assessment of acute toxicity: Virtually nontoxic after a single ingestion. Based on available Data, the classification criteria are not met.

# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27  
Version: 1.0

Page: 7/10  
(30367671/SDS\_GEN\_US/EN)

### Irritation / corrosion

Assessment of irritating effects: Eye contact causes irritation.

### Sensitization

Assessment of sensitization: Based on available Data, the classification criteria are not met.

## **Chronic Toxicity/Effects**

### Repeated dose toxicity

Assessment of repeated dose toxicity: This product contains crystalline silica (quartz). Prolonged or repeated inhalation of respirable crystalline silica may result in silicosis.

### Genetic toxicity

Assessment of mutagenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Carcinogenicity

Assessment of carcinogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### *Information on: crystalline silica*

*Assessment of carcinogenicity: In long-term studies in rats and mice in which the substance was given by feed, a carcinogenic effect was not observed. In long-term animal studies in which the substance was given by inhalation in high doses, a carcinogenic effect was observed. The substance and its compounds in the form of respirable dusts/aerosols classified by the German MAK commission as a category 1 carcinogen (substances that cause cancer to humans). A carcinogenic effect cannot safely be ruled out. The inhalation uptake of the alveolar fraction of the fine dust may cause damage to the lungs. The International Agency for Research on Cancer (IARC) has classified this substance as a Group 1 (known) human carcinogen.*

*NTP listed carcinogen*

### Reproductive toxicity

Assessment of reproduction toxicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Teratogenicity

Assessment of teratogenicity: The chemical structure does not suggest a specific alert for such an effect. Based on available Data, the classification criteria are not met.

### Other Information

Based on our experience and the information available, no adverse health effects are expected if handled as recommended with suitable precautions for designated uses. The product has not been tested. The statements on toxicology have been derived from the properties of the individual components.

## **Symptoms of Exposure**

The most important known symptoms and effects are described in the labelling (see section 2) and/or in section 11.

---

## **12. Ecological Information**

### **Toxicity**

# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27  
Version: 1.0

Page: 8/10  
(30367671/SDS\_GEN\_US/EN)

### Aquatic toxicity

#### Assessment of aquatic toxicity:

Based on available Data, the classification criteria are not met. There is a high probability that the product is not acutely harmful to aquatic organisms.

### Persistence and degradability

#### Assessment biodegradation and elimination (H2O)

Inherently biodegradable. The insoluble fraction can be removed by mechanical means in suitable waste water treatment plants.

The polymer component of the product is poorly biodegradable.

### Bioaccumulative potential

#### Assessment bioaccumulation potential

Discharge into the environment must be avoided.

### Mobility in soil

#### Assessment transport between environmental compartments

No data available.

### Additional information

#### Other ecotoxicological advice:

Do not discharge product into the environment without control. The product has not been tested. The statements on ecotoxicology have been derived from the properties of the individual components.

---

## 13. Disposal considerations

### Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Residues should be disposed of in the same manner as the substance/product. Do not discharge into drains/surface waters/groundwater.

### Container disposal:

Contaminated packaging should be emptied as far as possible; then it can be passed on for recycling after being thoroughly cleaned.

---

## 14. Transport Information

### Land transport

USDOT

Hazard class:	9
Packing group:	III
ID number:	UN 8888
Hazard label:	
Proper shipping name:	LOCKED FOR VALIDATION

### Sea transport

IMDG

Hazard class:	9
---------------	---



# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27  
Version: 1.0

Page: 9/10  
(30367671/SDS\_GEN\_US/EN)

ID number: UN 8888  
Hazard label: 9  
Marine pollutant: NO  
Proper shipping name: LOCKED FOR VALIDATION

### Air transport

IATA/ICAO

Hazard class: 9  
ID number: UN 8888  
Hazard label:  
Proper shipping name: LOCKED FOR VALIDATION

## 15. Regulatory Information

### Federal Regulations

#### Registration status:

Chemical TSCA, US released / listed

Registration status based on supplier confirmation

**EPCRA 311/312 (Hazard categories):** Acute; Chronic

### CERCLA RQ

1000 LBS

### CAS Number

7727-43-7; 108-88-3

### Chemical name

Barium sulfate; Toluene

100 LBS

107-98-2

1-methoxypropan-2-ol

10 LBS

71-43-2; 106-99-0

Benzene; butadiene

### State regulations

#### CA Prop. 65:

WARNING: THIS PRODUCT CONTAINS A CHEMICAL(S) KNOWN TO THE STATE OF CALIFORNIA TO CAUSE CANCER AND BIRTH DEFECTS OR OTHER REPRODUCTIVE HARM.

#### NFPA Hazard codes:

Health : 2 Fire: 2 Reactivity: 0 Special:

## 16. Other Information

#### SDS Prepared by:

BASF NA Product Regulations

SDS Prepared on: 2015/04/27

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our

# Safety Data Sheet

## MasterSeal TC 275 blk PART A also CONIPUR 275 TOP COAT BLACK PTA

Revision date : 2015/04/27

Page: 10/10

Version: 1.0

(30367671/SDS\_GEN\_US/EN)

operations on society and the environment during production, storage, transport, use and disposal of our products.

---

IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE , IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK.  
END OF DATA SHEET