

**SL 1**

Version 1.9

09/17/2007

**1. PRODUCT AND COMPANY INFORMATION**

Company	:	<b>BASF Building Systems, Inc.</b> 889 Valley Park Drive Shakopee, MN 55379
Telephone	:	952-496-6000
Emergency telephone number	:	BASF ER HOTLINE: 800-832-4357 CHEMTREC: 800-424-9300 CHEMTREC (Outside Continental US): 703-527-3887
Product name	:	SL 1
MSDS ID No.	:	10590
TSCA Inventory	:	All components of this product are included, or are exempt from inclusion, in the EPA Toxic Substances Control Act (TSCA) Chemical Substance Inventory.
Canadian DSL	:	All components of this product are included, or are exempt from inclusion, in the Canadian Domestic Substance List (DSL).
Product Use Description	:	Sealant

**2. HAZARDOUS INGREDIENTS**

<u>Chemical</u>	<u>CAS No.</u>	<u>TLV</u>	<u>STEL</u>	<u>PEL</u>	<u>CEIL</u>	<u>Weight %</u>
STODDARD SOLVENT	8052-41-3	100 ppm	N.E.	500 ppm	N.E.	3.00 - 7.00 %
CALCIUM OXIDE	1305-78-8	2 mg/m3	N.E.	5 mg/m3	N.E.	5.00 - 10.00 %
TALC	14807-96-6	2 mg/m3	N.E.	N.E.	N.E.	3.00 - 7.00 %
2,4-TOLUENE DIISOCYANATE	584-84-9	0.005 ppm0.04 mg/m3	0.02 ppm0.15 mg/m3	N.E.	0.02 ppm	3.00 - 7.00 %
TITANIUM DIOXIDE	13463-67-7	10 mg/m3	N.E.	15 mg/m3	N.E.	1.00 - 5.00 %
2,6 TOLUENE DIISOCYANATE	91-08-7	0.005 ppm	0.02 ppm	N.E.	N.E.	0.50 - 1.50 %

**3. HAZARDS IDENTIFICATION**

HMIS® Rating		HEALTH 2	FLAMMABILITY 2	PHYSICAL HAZARD 0
WHMIS Class	:	B3		
Primary Routes of Entry	:	Skin contact Inhalation Ingestion Eye contact		

**Effects of Overexposure**

Inhalation : Harmful by inhalation. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting. Inhalation of high vapor

**SL 1**

Version 1.9

09/17/2007

concentrations can cause CNS-depression and narcosis.

- Skin : Prolonged skin contact may defat the skin and produce dermatitis. Prolonged or repeated exposure can cause skin irritation and redness. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. May cause sensitization by skin contact.
- Eyes : Can cause moderate to severe irritation, redness, tearing and blurred vision.
- Ingestion : Irritating to mouth, throat and stomach. Intake can cause gastrointestinal irritation, nausea, and vomiting.
- Chronic exposure : This product contains solvents. Reports associate repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Reports also indicate that solvents cause liver damage, kidney damage, and mucous membrane irritation. Be warned that intentional misuse by deliberately inhaling the vapors and/or the product contents (a process often called "sniffing") can be harmful or fatal. Existing respiratory or skin ailments may be aggravated by exposure. This product contains a suspect carcinogen listed by IARC. This product contains a suspect carcinogen listed by NTP. This product contains a suspect carcinogen listed by OSHA.

**Carcinogenicity**

	ACGIH	IARC	NTP	OSHA
STODDARD SOLVENT	N.E.	No data.	N.E.	N.E.
CALCIUM OXIDE	N.E.	N.E.	N.E.	N.E.
TALC	Not classifiable as a human carcinogen.	Inadequate data.	N.E.	N.E.
2,4-TOLUENE DIISOCYANATE	Sensitiser.	No data.	Anticipated carcinogen.	N.E.
TITANIUM DIOXIDE	Not classifiable as a human carcinogen.	Regard as if carcinogenic for man.	N.E.	N.E.
2,6 TOLUENE DIISOCYANATE	Sensitiser.	No data.		N.E.

**4. FIRST AID MEASURES**

- Eye contact : Flush eyes with water, lifting upper and lower lids occasionally for 15 minutes. Seek medical attention.
- Skin contact : Remove contaminated clothing. Wash thoroughly with soap and water. If irritation persists seek medical attention. Wash contaminated clothing before reuse.
- Ingestion : Do not induce vomiting without medical advice. If conscious, drink plenty of water. If a person feels unwell or symptoms of skin irritation appear, consult a physician. If a person vomits, place him/her in the recovery position. Never give anything by mouth to an unconscious person.
- Inhalation : Remove victim from exposure. If difficulty with breathing, administer oxygen. If breathing has stopped administer artificial respiration, preferably mouth-to-mouth. Seek immediate medical attention.

**5. FIRE-FIGHTING MEASURES**

- Flash point : 145.00 °F (62.78 °C) Method: Taglibue C. C.
- Autoignition temperature : no data available

**SL 1**

Version 1.9

09/17/2007

Lower explosion limit	:	0.9 %(V)
Upper explosion limit	:	9.5 %(V)
Suitable extinguishing media	:	carbon dioxide (CO <sub>2</sub> ) dry chemical water fog
Fire and Explosion Hazards	:	Combustible Liquid. Can form explosive mixtures at temperatures at or above the flashpoint. Vapors can travel to a source of ignition and flash back. Empty containers retain product residue (liquid and/or vapor) and can be dangerous. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; CONTAINERS MAY EXPLODE AND CAUSE INJURY OR DEATH. DO NOT PRESSURIZE, CUT, WELD, BRAZE, SOLDER, DRILL, GRIND, OR EXPOSE SUCH CONTAINERS TO HEAT, FLAME, SPARKS, STATIC ELECTRICITY, OR OTHER SOURCES OF IGNITION; CONTAINERS MAY EXPLODE AND CAUSE INJURY OR DEATH. Solid stream of water or foam can cause frothing.
Special Fire-fighting Procedures	:	At higher temperature pressure build up in sealed containers. Use water to cool containers exposed to fire. As in any fire, wear pressure demand self-contained breathing apparatus (NIOSH approved or equivalent) and full protective gear.

---

**6. ACCIDENTAL RELEASE MEASURES**

---

Methods for cleaning up	:	Ventilate the area and remove all sources of ignition. Evacuate unnecessary personnel. Take action to eliminate source of leak. Large spills should be handled carefully. Put on respiratory protection and necessary personal protective equipment. Dike or impound spilled Liquid. Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).
-------------------------	---	--

---

**7. HANDLING AND STORAGE**

---

Handling	:	Use only in area provided with appropriate ventilation. Keep out of reach of children. Take precautionary measures against static discharges. Ground and bound containers when transferring material. For personal protection see section 8.
Storage	:	Keep containers tightly closed in a dry, cool and well-ventilated place.

---

**8. EXPOSURE CONTROLS / PERSONAL PROTECTION**

---

Eye protection	:	Wear as appropriate: safety glasses with side-shields goggles face-shield
Hand protection	:	Wear Chemically resistant gloves.
Body Protection	:	Wear as appropriate: Chemically resistant clothes preventive skin protection

**SL 1**

Version 1.9

09/17/2007

- Respiratory protection : In case of insufficient ventilation wear suitable respiratory equipment. When workers are facing concentrations above the exposure limit they must use NIOSH approved respirators.
- Hygienic Practices : Avoid contact with skin, eyes and clothing. Ensure adequate ventilation, especially in confined areas. Wash hands before breaks and at the end of workday. When using, do not eat, drink or smoke. Handle in accordance with good industrial hygiene and safety practice.
- Engineering Controls : Local exhaust ventilation can be necessary to control any air contaminants to within their TLVs during the use of this product.

---

**9. PHYSICAL AND CHEMICAL PROPERTIES**

---

- Color : various colors
- Physical State : liquid
- Odor : solvent
- pH : not applicable
- Odor Threshold : no data available
- Vapor Pressure : no data available
- Vapor Density : Heavier than air
- Boiling point/range : 187.00 - 484.00 °F (86.11 - 251.11 °C)
- Freeze Point : no data available
- Water solubility : slightly soluble
- Specific Gravity : 1.10
- Viscosity : 325 poise
- Evaporation rate : Slower than Butyl acetate
- Partition coefficient (n-octanol/water) : no data available
- VOC Concentration as applied (less water and exempt solvents) : 104 g/l

---

**10. STABILITY AND REACTIVITY**

---

- Stability : Stable under recommended storage conditions.
- Conditions to avoid : Heat, flames and sparks.  
Prolonged exposure to high temperatures
- Materials to avoid : strong oxidizing agents

**SL 1**

Version 1.9

09/17/2007

Hazardous decomposition products : Oxides of carbon.  
Thermal decomposition can lead to release of irritating gases and vapours.

Hazardous polymerization : Will not occur when handled according to manufacturer's instructions.

**11. TOXICOLOGICAL INFORMATION**

**Acute inhalation toxicity**

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>	<u>Exposure time</u>
	LC50	no data available		
<u>Component</u>				
STODDARD SOLVENT	LC50	no data available		
CALCIUM OXIDE	LC50	no data available		
TALC	LC50	no data available		
2,4-TOLUENE DIISOCYANATE	LC50	no data available		
TITANIUM DIOXIDE	LC50	no data available		
2,6 TOLUENE DIISOCYANATE	LC50	no data available		

**Acute oral toxicity**

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Oral)	no data available	
<u>Component</u>			
STODDARD SOLVENT	LD50 (Oral)	no data available	
CALCIUM OXIDE	LD50 (Oral)	no data available	
TALC	LD50 (Oral)	no data available	
2,4-TOLUENE DIISOCYANATE	LD50 (Oral)	no data available	
TITANIUM DIOXIDE	LD50 (Oral)	no data available	
2,6 TOLUENE DIISOCYANATE	LD50 (Oral)	100 mg/kg	

**Acute dermal toxicity**

<u>Product</u>	<u>Type</u>	<u>Value</u>	<u>Species</u>
	LD50 (Dermal)	no data available	
<u>Component</u>			
STODDARD SOLVENT	LD50 (Dermal)	no data available	
CALCIUM OXIDE	LD50 (Dermal)	no data available	
TALC	LD50 (Dermal)	no data available	
2,4-TOLUENE DIISOCYANATE	LD50 (Dermal)	no data available	
TITANIUM DIOXIDE	LD50 (Dermal)	no data available	

**SL 1**

Version 1.9

09/17/2007

2,6 TOLUENE DIISOCYANATE

LD50 (Dermal) no data available

**12. ECOLOGICAL INFORMATION**

Ecotoxicological Information : There is no data available for this product.

**13. DISPOSAL CONSIDERATIONS**

Recommendations: Use excess product in an alternate beneficial application. Handle disposal of waste material in manner which complies with local, state, province and federal regulation.

**14. TRANSPORT INFORMATION**

DOT : Proper shipping name Not regulated

IATA : Proper shipping name Not regulated

**15. REGULATORY INFORMATION****SARA 311/312 (RTK)**

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendments and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

IMMEDIATE (ACUTE) HEALTH HAZARD DELAYED (CHRONIC) HEALTH HAZARD FIRE HAZARD

**SARA 313**

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372:

<u>Weight %</u>	<u>CAS No.</u>	<u>Chemical Name</u>
3.00 - 7.00 %	584-84-9	2,4-TOLUENE DIISOCYANATE
0.50 - 1.50 %	91-08-7	2,6 TOLUENE DIISOCYANATE

**CERCLA**

CERCLA section 103(a) specifically requires the person in charge of a vessel or facility to report immediately to the National Response Center (NRC) a release of a hazardous substance whose amount equals or exceeds the assigned RQ. The following hazardous substances are contained in this product.

<u>RQ</u>	<u>CAS No.</u>	<u>Chemical Name</u>
100 lbs	584-84-9	2,4-TOLUENE DIISOCYANATE
100 lbs	91-08-7	2,6 TOLUENE DIISOCYANATE

**TSCA Section 12(b) Export Notification**

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(b) if exported from the United States:

<u>CAS No.</u>	<u>Chemical Name</u>
75-35-4	1,1-DICHLOROETHYLENE

**SL 1**

Version 1.9

09/17/2007

**California Proposition 65**

The chemical(s) noted below and contained in this product, are known to the state of California to cause cancer, birth defects or other reproductive harm. Unless otherwise specified in Section 2 of this MSDS, these chemicals are present at < 0.1%:

<u>CAS No.</u>	<u>Chemical Name</u>
100-41-4	ETHYLBENZENE
7440-43-9	CADMIUM
7440-38-2	ARSENIC
7440-02-0	NICKEL
7439-92-1	INORGANIC LEAD
1333-86-4	CARBON BLACK
71-43-2	BENZENE
107-13-1	ACRYLONITRILE
108-88-3	TOLUENE
14808-60-7	SILICA, CRYSTALLINE QUARTZ

**16. OTHER INFORMATION**

Legend	:	N.E. - Not Established TLV - Threshold Limit Value STEL - Short Term Exposure Limit PEL - Permissible Exposure Limit CEIL - Ceiling
Prepared By	:	Environment, Health and Safety Department

This information is furnished without warranty, representation, or license of any kind, except that this information is accurate to the best of the manufacturer's knowledge, or is obtained from sources believed by the manufacturer to be accurate and is not intended to be all inclusive. No warranty is expressed or implied regarding the accuracy of this information or the results to be obtained from its use thereof. The manufacturer assumes no responsibility for injuries proximately caused by use of the Material if reasonable safety procedures are not followed as stipulated in this Data Sheet. Additionally, the manufacturer assumes no responsibility for injuries proximately caused by abnormal use of the Material even if reasonable safety procedures are followed. Buyer assumes the risk in its use of the Material.

End of MSDS.