

1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product name: Other name: Product code: Recommended Use:	SONOLASTIC NP2/SL2 PIGMENTS None allocated Various Pigment paste for Sonolastic NP2/SL2 sealant systems.
Company:	BASF Construction Chemicals Australia Pty Ltd.
ABN:	46 000 450 288
Address:	11 Stanton Road, Seven Hills, NSW, 2147, Australia
Telephone number:	+61 2 8811 4200
Facsimile:	+61 2 8811 3299
Company:	BASF Construction Chemicals New Zealand Ltd.
Address:	45 William Pickering Drive,
	Albany, Auckland,
	New Zealand
Telephone number:	+64 9 414 7233
Facsimile:	+64 9 414 7244
Emergency telephone number:	0417 658 263

2. HAZARDS IDENTIFICATION

Hazard classification:	Hazardous according to criteria of NOHSC
Risk phrase(s):	None allocated
Safety phrase(s):	None allocated

3. COMPOSITION / INFORMATION ON INGREDIENTS

INGREDIENTS

Chemical Name	CAS Number	Proportion
Carbon Black	1333-86-5	10 -< 30%
Ferric Oxide	1309-37-1	10 -< 30%
Non-hazardous ingredients		to 100%

4. FIRST AID MEASURES

Ingestion: Do NOT induce vomiting. Wash mouth with water and seek medical attention.

Eyes: While holding eyes open, gently flood with plenty of fresh water for 15 minutes. If irritation persists or recurs seek medical attention. Skilled personnel should only undertake removal of contact lenses after an eye injury.

Skin: Remove contaminated clothing. Flush contacted area thoroughly with soap and plenty of water. If irritation persists, seek medical attention. If irritation persists seek medical attention.

BASF Material Safety Data Sheet according to NOHSC: 2011 (2003)SONOLASTIC NP2/SL2 PIGMENTSPage 1 of 4



Inhalation: Remove to fresh air. If breathing is difficult, give oxygen and seek medical attention immediately.

First aid facilities: Ensure availability of clean water for eye/skin wash. Advice to doctor: Treat symptomatically.

5. FIRE FIGHTING MEASURES

Suitable extinguishing media:	Foam, CO_2 and Dry Chemical.
Hazards from combustion products:	Acrid fumes and oxides of carbon.
Precautions and equipment for fire fighters:	Full protective clothing with self-contained breathing apparatus as per personal protection, section 8.
Hazchem code:	None allocated

6. ACCIDENTAL RELEASE MEASURES

Methods for clean up / collecting:	Small or major spills should be adsorbed with dry, inert filler (soil or sand) which then can be shovelled into appropriately labelled drums for disposal. Ventilate the area and remove all sources of ignition.
Environmental precautions:	Do not discharge into sewers.

7. HANDLING AND STORAGE

Conditions for safe storageLocation:Store in a cool, dry and well-ventilated area.Temperature conditions:5 to 35°C. Avoid long-term exposure to elevated temperatures.Protection from weather:Store undercover and away from moisture, heat and direct sunlight.Storage incompatibilities:Strong bases or oxidants. Strong Lewis or mineral acids.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure standards: Engineering controls:	Not available Ventilation is recommended under normal use conditions. State regulations on speed and direction of airflow away from operators must be observed. Keep containers closed when not in use. Keep out of reach of children.
Personal protective equipment	
Respiratory protection:	Type A1 if ventilation is inadequate.
Glove type (AS2161):	Long PVC or nitrile rubber gauntlets
Eye protection:	Chemical worker's goggles.
Clothing:	Overalls.
Other:	Use barrier creams to protect skin from contact with the material. Always wash hands before smoking, eating, drinking or using the toilet and after finishing work. Observe the usual precautions when handling chemicals.

9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Pigmented paste with mild odour
Boiling point (°C):	Not available

BASF Material Safety Data Sheet according to NOHSC: 2011 (2003)SONOLASTIC NP2/SL2 PIGMENTSPage 2 of 4



Melting point (°C): Vapour pressure @ 25°(kPa): Specific gravity: Flash point (°C): Flammability limits (%):

Solubility in water: Evaporation rate: Not applicable Not applicable > 1.0 > 193 UEL – Not applicable LEL – Not applicable Insoluble Slower than butyl acetate

10. STABILITY AND REACTIVITY

Hazard of use/storage:Stable under normal storage and application temperature.Materials to avoid:Strong bases or oxidants. Strong Lewis or mineral acids.Hazardous decomposition products:Acrid fumes and oxides of carbon.

11. TOXICOLOGICAL INFORMATION

<u>Acute</u>

Ingestion:	May cause irritation to mouth, throat and stomach.
Eye:	May cause slight irritation.
Skin:	May causes slight irritation.
Inhalation:	May causes respiratory tract irritation.

<u>Chronic</u>: Susceptible individuals may develop allergic reactions such as dermatitis on a single significant skin or respiratory exposure or may become sensitised to the material on repeated and prolonged contact. Hence it is imperative that all forms of exposure be kept to an absolute minimum.

12. ECOLOGICAL INFORMATION

Ecology:

Do not discharge into sewers.

13. DISPOSAL CONSIDERATIONS

Disposal MethodsState/Territory authority:Observe all Federal, State and Local regulationsDispose – Secure landfill:Yes.Dispose – High temp incinerator:YesPrecautions for clean up crew:Full protective clothing as per personal protection, section 8.

14. TRANSPORT INFORMATION

UN number:	None allocated
Dangerous goods class:	None allocated
Subsidiary risk:	None allocated
EPG card:	None allocated
Shipping name:	None allocated

BASF Material Safety Data Sheet according to NOHSC: 2011 (2003)SONOLASTIC NP2/SL2 PIGMENTSPage 3 of 4



Packing group:	None allocated
Poisons schedule:	None allocated
Hazchem code:	None allocated

15. REGULATORY INFORMATION

Risk phrase(s):None allocatedSafety phrase(s):None allocated

16. OTHER INFORMATION

Reason for Issue: Change of company name.

This MSDS summarises our best knowledge of the health and safety hazard information of the product and how to safely handle and use the product in the workplace. Each user should read this MSDS and consider the information in the context of how the product will be handled and used in the workplace including in conjunction with other products. If clarification or further information is needed to ensure that an appropriate risk assessment can be made, the user should contact this company. Our responsibility for products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request. All information contained in this MSDS is as accurate and up-to-date as possible. No warranty expressed or implied is made as to its accuracy, reliability or completeness.