

**EUCO QWIKJOINT 200 PART B - 50 GALLON**Version 1.2
REVISION DATE: 09/21/2007

Print Date 10/23/2008

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : EUCO QWIKJOINT 200 PART B - 50 GALLON
 Product code : 693B 55

COMPANY : Euclid Chemical Company
 19218 Redwood Road
 Cleveland, OH 44110

Telephone : 1-800-321-7628
 Emergency Phone: : U.S. only: 1-800-255-3924
 International Users Call Collect: 1-813-248-0585

Product use : Curative

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Clear. Liquid solution. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause slight irritation to the respiratory system.
 Eyes : Vapors or liquid may cause tearing, blurred vision, severe irritation, and possible chemical burns.
 Ingestion : May cause irritation to the mouth, throat and stomach. May cause chemical burns to stomach, mouth, nose, and throat.
 Skin : May cause moderate irritation. May cause sensitization resulting in irritation, itching and redness.

Aggravated Medical Conditions

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Prolonged and repeated overexposure to amines may cause liver and kidney damage based on animal studies. Animal studies have shown adverse effects in the pancreas, liver, thyroid and eyes caused by diethyltoluenediamine (DETDA). In rare instances, sensitization to DETDA has been reported to occur in humans. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Lung

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Diisodecyl phthalate	26761-40-0	> 60.0
Diethyltoluenediamine	68479-98-1	15.0 - 40.0
Propoxylated Amine	102-60-3	3.0 - 7.0
6-Methyl-2,4-di(methylthio)-1,3-	102093-68-5	3.0 - 7.0



EUCO QWIKJOINT 200 PART B - 50 GALLON

Version 1.2
 REVISION DATE: 09/21/2007

Print Date 10/23/2008

benzenediamine		
Amorphous silica	7631-86-9	1.0 - 5.0
Titanium dioxide	13463-67-7	1.0 - 5.0
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	<0.1

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for 15 minutes. If irritation persists, get medical attention.
- Skin contact : Wash area of contact thoroughly with hand cleaner followed by soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : > 200 °F, > 93 °C
- Method : Closed Cup
- Lower explosion limit : Not available.
- Upper explosion limit : Not available.
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Carbon monoxide, carbon dioxide, and nitrogen oxides.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA).
- Fire and explosion conditions : Product may ignite if heated in excess of its flash point.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

SECTION 7 - HANDLING AND STORAGE

Store under normal warehouse conditions in sealed containers. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container. Change soiled work clothes frequently. Clean hands thoroughly after handling. Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Handle in compliance with common hygienic practices. Clean hands thoroughly after handling.



EUCO QWIKJOINT 200 PART B - 50 GALLON

Version 1.2
 REVISION DATE: 09/21/2007

Print Date 10/23/2008

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Use full engineering controls before relying on personal protective equipment. Wear NIOSH/MSHA approved vapor respirator with appropriate cartridge when the vapor concentration is expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Protect hands with impervious gloves.
- Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use.
- Engineering measures : Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Amorphous silica	7631-86-9	ACGIH TWA:	3 mg/m3	Respirable particles.
		ACGIH TWA:	10 mg/m3	Inhalable particles.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA TWA:	0.8 mg/m3	
Titanium dioxide	13463-67-7	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Crystalline Silica (Quartz)/ Silica Sand	14808-60-7	OSHA TWA:	0.1 mg/m3	Respirable.
		OSHA TWA:	0.3 mg/m3	Total dust.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA PEL:	5 mg/m3	Respirable fraction.
		ACGIH TWA:	0.025 mg/m3	Respirable fraction.

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

- Form : Liquid solution
- Color : Clear
- Odor : Slight
- pH : Not available.
- Vapour pressure : Not available.
- Vapor density : Not available.
- Melting point/range : Not available.
- Freezing point : Not available.



EUCO QWIKJOINT 200 PART B - 50 GALLON

Version 1.2
REVISION DATE: 09/21/2007

Print Date 10/23/2008

Boiling point/range : Not available.
Water solubility : Not available.
Specific Gravity : 1.1
% Volatile Weight : 0.0 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid : Acids.
Stability : Stable under normal conditions. Avoid welding arcs, flames or other high temperature sources.
Hazardous polymerization : Will not occur under normal conditions.

SECTION 11 - TOXICOLOGICAL INFORMATION

Amorphous silica, CAS-No.: 7631-86-9
Acute oral toxicity (LD-50 oral) : 22,500 mg/kg (Rat) 22,500 mg/kg (Rat) 15,000 mg/kg (Mouse) 15,000 mg/kg (Mouse)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.


SECTION 14 - TRANSPORTATION / SHIPPING DATA

TDG / DOT Shipping Description:
NOT REGULATED

SECTION 15 - REGULATORY INFORMATION

North American Inventories:
All components are listed or exempt from the TSCA inventory.
This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:
SARA 313 Components : None present or none present in regulated quantities.



EUCO QWIKJOINT 200 PART B - 50 GALLON

Version 1.2
 REVISION DATE: 09/21/2007

Print Date 10/23/2008

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components :
 Amorphous silica 7631-86-9
 Titanium dioxide 13463-67-7
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

OSHA Status: Considered : Irritant
 hazardous based on the
 following criteria:

OSHA Flammability : Not Regulated

Regulatory VOC (less water and
 exempt solvent) : 0 g/l
 VOC Method 310 : 0 %

U.S. State Regulations:

MASS RTK Components : Amorphous silica 7631-86-9
 Titanium dioxide 13463-67-7
 Crystalline Silica (Quartz)/ Silica Sand 14808-60-7

Penn RTK Components : Diisodecyl phthalate 26761-40-0
 Diethyltoluenediamine 68479-98-1
 Propoxylated Amine 102-60-3
 6-Methyl-2,4-di(methylthio)-1,3-
 benzenediamine 102093-68-5
 Amorphous silica 7631-86-9
 Titanium dioxide 13463-67-7

NJ RTK Components : Diisodecyl phthalate 26761-40-0
 Diethyltoluenediamine 68479-98-1
 Propoxylated Amine 102-60-3
 6-Methyl-2,4-di(methylthio)-1,3-
 benzenediamine 102093-68-5
 Amorphous silica 7631-86-9
 Titanium dioxide 13463-67-7

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm:

1333-86-4 Carbon Black
 117-81-7 Dioctyl phthalate

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	2
Reactivity	1
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe



EUCO QWIKJOINT 200 PART B - 50 GALLON

Version 1.2
REVISION DATE: 09/21/2007

Print Date 10/23/2008

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System