SAFETY DATA SHEET

-										
SECTION I: I	DENTIF	ICATION								
PRODUCT FillPro™		Standard Backer Rod, FillPro™			MANUFACTURER NAME & ADDRESS:					
IDENTIFIER:	Type Bac	ker Rod, FillPro™	er Rod, FillPro™ Hot Rod XL		MANUFACTURER NAME & ADDRESS:					
CHEMICAL	POLYETHYLENE				ARMACELL CANADA Inc.					
IDENTITY:	FOLIETHILLING				153 VAN KIRK DRIVE					
RECOMMENDED		,	SOUND DAMPENING,		BRAMPTON, ONTARIO , L7A 1A4					
USE		ON, SEALING, FLOATATION etc.			PHONE NO.:		1-905-846-3666			
RESTRICTION OF NONE					FAX NO.:		1-905-846-0363			
USE					EMERGENCY PH	IONE NO.:	1-800-387-3847			
OFOTION O. I	SECTION 2 : HAZARD(S) IDENTIFICATION									
		. ,								
					ED BY OSHA AS "I					
- PE FOAM PRODU	JCTS ARE	MADE FROM P	OLYETHYLEN	NE RESIN	, ADDITIVES AND	ISOBUTANE	.(MORE DETAILS IN SEC.3.)			
- ISOBUTANE, A F	LAMABLE	HYDROCARBO	N IS USED A	S BLOW	NG AGENT.SMALL	TRACES C	F THIS GAS MAY BE			
							NS ABOVE THE LOWER			
FLAMMABLE LIMIT	S (LFL) IF	LARGE QUANT	ITIES OF TH	IS PROD	UCT ARE STORED	IN UNVENT	TILATED AREAS.			
ROUTES OF EXPOSURE:	SWALLO	WING SKIN	ABSORBTIO	N	INHALATION	SKIN CO	NTACT EYE CONTACT			
EFFECTS OF A SIN		IITE) OVEREYD	OSLIDE BV:							
SWALLOWING:	NGLL (AC			I OCKAG						
SKIN ABSORBTIO	NI.	CHOKING - MECHANICAL BLOCKAGE								
	IN:		NOT LIKELY. FOAM DUST MAY CAUSE RRITATION TO NOSE ,THROAT OR LUNGS.							
INHALATION:					•	AT OR LUN	GS.			
SKIN CONTACT:		NON IRRITATING TO SKIN CONTACT								
EYE CONTACT:		EYE INJURY OR FOAM DUST MAY CAUSE IRRITATION TO EYES								
OTHER EFFECTS		NOT KNOWN								
SECTION 3 : COI	MPOSITION	ON / INFORMA	TION ON IN	GREDIE	NTS					
INGREDIEN	TS	CAS NO. WEIGHT %		EXPOSURE LIMITS ACGIH - TLV*						
INGREDIENTS		OAO NO.	o. Welom 70							
POLYETHYLENE		9002-88-4	75%	-100%		N	IA			
ISOBUTANE		75-28-5		-	800 PPM TWA					
CARBON BLACK		1333-86-4	0.5%	6 - 5 %	3.5 mg/m ³					
* Applicable provincial	TLV's may	differ			•					
* Specific chemical na	mes and pe	ercentage in the mix	has been with	held to pro	tect trade secret.					
		<u> </u>								
SECTION 4 : FIR	ST AID M	IEASURES								
SWALLOWING:				SKIN C	ONTACT:					
CONSULT PHYSIC	IAN				WASH WITH SOAP AND WATER					
					EYE CONTACT:					
					SH EYES WITH CLEAN LUKEWARM WATER. CONSULT					
					PHYSICIAN.					
DREATHING FRODELINO FEROIOTO.										
SECTION 5 : FIRE FIGHTING MEASURES										
1. PE FOAM IS COMBUSTIBLE AND SHOULD NOT BE EXPOSED TO SPARKS OR OPEN FLAME. RESULTS IN CLASS A FIRE.										
2. FIRE TO BE EXTINGUISHED BY USING WATER FOG OR FINE SPRAY. SOAK THE PRODUCT WITH WATER TO COOL AND SMOTHER.										
3. FIRE WILL CAUSE DENSE SMOKE. USE SELF-CONTAINED BREATHING APPRATUS AND FULL PROTECTIVE CLOTHING.										
4. FIRE WILL RESULT IN INTENSE HEAT AND SMOLDERING. EXTINGUISHMENT IS BY COOLING WITH WATER.										
5. OTHER FIRE EXTINGUISHERS (DRY CHEMICAL, FOAM OR CO2 EXTINGUISHERS) MAY BE USED FOR EXTINGUISHMENT.										
6. CHEMICAL/GASEC	OUS HAZAF	RDS LIKE CO, CO2	AND CARBON	MAY BE	PRODUCED FROM T	HE SMOLDE	RING SUBSTANCES AND FIRE.			
SECTION 6: A										
						AME, RESU	LTS IN CLASS 'A' FIRE.			

SAFETY DATA SHEET

SECTION 7: HANDLING AND STORAGE

- PE FOAM IS COMBUSTIBLE AND SHOULD NOT BE EXPOSED TO SPARKS OR OPEN FLAME. WHEN BURNS, WILL RELEASE TOXIC GASES LIKE CO.
- -WHEN FABRICATING OR CUTTING, THIS PRODUCT MAY RELEASE TRAPPED ISOBUTANE FROM THE FOAM CELLS. ADEQUATE VENTILATION IS A MUST.
- PE FOAM SHOULD BE STORED IN COOL,DRY AND WELL VENTILATED LOCATIONS. ISOBUTANE GAS MAY ACCUMULATE AROUND THE PRODUCT.
- PE FOAM IS INCOMPATIBLE WITH STRONG OXIDIZING AGENTS LIKE, CL2 .H2O2 , KNO3 ,H2SO4.

SECTION 8: EXPOSURE CONTROLS / PERSONAL PROTECTION

- NOT NECESSARY OTHER THAN STATED IN SECTION 2

SECTION 9: PHYSICA	AL AND CHEMI	CAL PROPERTIES			
PHYSICAL STATE:	SOLID	FREEZING POINT:	N/A	SPECIFIC GRAVITY VAPOUR	N/A
BOILING POINT 760 mm Hg:	N/A	VAP. PRESS at 20°C:	N/A	MOLECULAR WEIGHT:	N/A
SPECIFIC GRAVITY	0.01 - 0.15	SOLUBILITY IN WATER	INSOLUBLE	COEFFICIENT OF WATER /	N/A
MELTING POINT:	+ 212°F	EVAPORATION RATE	N/A	OIL DISTRIBUTION:	IN/A
DENSITY	0.5-30 lbs/cuft	% VOLATILES BY VOLUME:	N/A	VAPOUR DENSITY	N/A
APPEARANCE	CLOSED CELL FOAM	ODOR:	NEGLIGIBLE	ODOR THRESHOLD:	N/A

SECTION 10: STABILITY AND REACTIVITY

- PE FOAM IS STABLE AND NON-REACTIVE. OTHER THAN CONDITIONS STATED IN SECTION 5,6 & 7

SECTION 11: TOXICOLOGICAL INFORMATION

- PE FOAM HAS NO CARCINGENIC SUBSTANCES. IT IS NOT LISTED IN: IARC & NTP

ROUTES OF EXPOSURE: SWALLOWING FOAM DUST INHALATION SKIN CONTACT EYE CONTACT EFFECTS OF ABOVE EXPOSURE STATED IN SECTION 4

SECTION 12: ECOLOGICAL INFORMATION

- PE FOAM DOES NOT EXHIBIT ANY SIGNIFICANT BIODEGRADATION.

SECTION 13: DISPOSAL CONSIDERATIONS

- PE FOAM CAN BE REPROCESSED OR CAN BE DISPOSED OFF IN LANDFILL

SECTION 14: TRANSPORT INFORMATION

- PE FOAM HAS SOME RESIDUAL ISOBUTANE AND HENCE TO BE TRANSPORTED IN VENTILATED TRAILERS.

SECTION 15: REGULATORY INFORMATION

- PE FOAM HAS NO CARCINGENIC SUBSTANCES AND IS CLASSIFIED AS NON HAZARDOUS UNDER THE FEDERAL OSHA STANDARDS.

SECTION 16: OTHER INFORMATION

PREPARED BY / DEPARTMENT	PHONE NUMBER	DATE UPDATED
HARENDRA RATHOD / QA DEPARTMENT	905-846-3666 / 1-800-387-3847	March 17, 2016

FOR INFORMATION: Visit Web: www.tundrafoam.com or Email: info@tundrafoam.com