

Safety Data Sheet

Printing date 03/25/2015

Version Number 1.0

Reviewed on 03/25/2015

Page 1/8

1 Identification

Product identifier

Trade name: Bituthene Liquid Membrane Part A

SDS ID Number: 60025

Relevant identified uses of the substance or mixture and uses advised against Specialty construction product. Not intended for other uses

Details of the supplier of the safety data sheet

Manufacturer/Supplier:

W.R. Grace & Co. -Conn. 62 Whittemore Avenue Cambridge, MA 02140 USA

Grace Canada, Inc. 294 Clements Road W. Ajax, Ontario L1S 3C6 Canada

Information department:

Environmental Health & Safety USA: +1-617-876-1400 (24 hours) +1-800-354-5414 (8AM - 5PM) Not functional within Massachusetts CAN: 1-905-683-8561 (24 hours)

Transport Emergency: Chemtrec +1-800-424-9300 (24 hours)

2 Composition/information on ingredients

Chemical characterization: Mixtures

Description: Mixture of the substances listed below with additional nonhazardous ingredients.

Hazardous components:			
8052-42-4 Asphalt	20-25%		
64742-04-7 Extracts (petroleum), heavy paraffinic distillate solvent	10-20%		
Polycyclic Aromatic Hydrocarbons	0.1-1.0%		

Additional information: For the wording of the listed risk phrases refer to section 16.

3 Hazard(s) identification

Classification of the substance or mixture

May cause cancer.

GHS label elements The product is classified and labeled according to the Globally Harmonized System (GHS).

Hazard pictograms



Reviewed on 03/25/2015

Trade name: Bituthene Liquid Membrane Part A

Danger

Hazard-determining components of labeling: Asphalt Extracts (petroleum), heavy paraffinic distillate solvent Polycyclic Aromatic Hydrocarbons **Precautionary statements** Wear protective gloves/protective clothing/eye protection/face protection. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. IF exposed or concerned: Get medical advice/attention. Dispose of contents/container in accordance with local/regional/national/international regulations.

Additional information: Avoid breathing dust.

Hazard description: Harmful NFPA ratings (scale 0 - 4)

Health = 2Fire = 1Reactivity = 1

HMIS-ratings (scale 0 - 4)

HEALTH *2 Health = *2FIRE 1 Flammability = 1Reactivity = 1**REACTIVITY** 1

Other hazards Contact with residue from adhesive may cause eye and skin irritation.

4 First-aid measures

General information: Get medical advice/attention if you feel unwell.

After inhalation:

If symptoms develop, supply fresh air. If required, provide artificial respiration and seek immediate medical treatment.

After skin contact:

Immediately wash contaminated skin with soap or mild detergent and water. If this chemical soaks clothing, immediately remove clothing and wash skin.

If residue remains, clean with waterless handcream or abrasive soap. Never use solvents.

After eye contact:

If contact with residue causes eye irritation, flush eyes with water for at least 15 minutes while holding eyelids open.

Rinse cautiously with water for several minutes.

After swallowing: Do not induce vomiting; immediately call for medical help.

5 Fire-fighting measures

Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fire with alcohol resistant foam.

Special hazards arising from the substance or mixture No further relevant information available. (Cont. on page 3)

(Cont. from page 1)

Safety Data Sheet

Version Number 1.0

Trade name: Bituthene Liquid Membrane Part A

Additional information

Cool endangered receptacles with water spray.

Collect contaminated fire fighting water separately. It must not enter the sewage system.

6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Environmental precautions: Do not allow product to reach sewage system or any water course.

Methods and material for containment and cleaning up:

Contain and/or absorb spill with inert material (i.e. sand, vermiculite) then place in a suitable container.

Sweep up spilled product into receptacles.

Pick up mechanically.

Dispose contaminated material as waste according to section 13 of the SDS.

Reference to other sections

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and storage

Handling:

Precautions for safe handling

Prevent formation of aerosols.

Avoid eye and skin contact with residue from adhesive.

To avoid skin contact, use gloves. Clean hands after contact with adhesive residue.

Information about protection against explosions and fires: Keep respiratory protective device available.

Storage:

Information about storage in one common storage facility: Keep respiratory protective device available. **Further information about storage conditions:**

Specific end use(s) No further relevant information available.

8 Exposure controls/personal protection

Additional information about design of technical systems: No further data; see item 7.

Components with limit values that require monitoring at the workplace:

69012-64-2 Silica, fume

TLV (USA) TLV withdrawn

(Cont. on page 4)

USGHS

Reviewed on 03/25/2015

Reviewed on 03/25/2015

Version Number 1.0

Trade name: Bituthene Liquid Membrane Part A

	(Cont. from page 3)		
8052-42-4 A	Asphalt		
REL (USA)	Ceiling limit value: 5* mg/m ³ *15-min; See Pocket Guide App. A		
TLV (USA)	Long-term value: 0.5* mg/m ³ *inh. fraction; as benzene-soluble aerosol; BEIp		
Ingredients	Ingredients with biological limit values:		
8052-42-4 A	Asphalt		
BEI (USA)	-		
	Medium: urine		
	Time: end of shift at end of workweek		
	Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)		
Polycyclic .	Polycyclic Aromatic Hydrocarbons		
BEI (USA)	Medium: urine		
	Time: end of shift at end of workweek		
	Parameter: 1-Hydroxypyrene with hydrolysis (nonquantitative)		

Additional information: The lists that were valid during the creation were used as basis.

Personal protective equipment:

General protective and hygienic measures:

The usual precautionary measures for handling chemicals should be followed.

Store protective clothing separately.

Breathing equipment:

A chemical cartridge respirator with organic vapor cartridge is required. A dust/mist cartridge or prefilter may be needed in addition to control exposure to mist. Supplied air respirator (SCBA) is required at exposure levels above the capabilities of a chemical cartridge respirator.

Respiratory protection is not normally required. If exposures exceed PELs use a NIOSH approved organic vapor respirator.

Protection of hands:

Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Material of gloves

Gloves should be worn to prevent skin contact and should be impermeable and resistant to the product.

Eye protection:



Safety glasses with side shield protection.



A face shield should also be worn if there is potential exposure to splash or spray.

Body protection:

Use personal protective equipment as required.

Take off contaminated clothing and wash before reuse.

USGHS (Cont. on page 5)

Trade name: Bituthene Liquid Membrane Part A

(Cont. from page 4)

Reviewed on 03/25/2015

General Information		
Appearance:		
Form:	Liquid	
Color:	According to product specification	
Odor: Odour threshold:	Characteristic Not determined.	
pH-value (~):	Not determined.	
Change in condition		
Melting point/Melting range:	Undetermined.	
Boiling point/Boiling range:	Undetermined.	
Flash point:	200 °C (392 °F)	
Flammability (solid, gaseous):	Not applicable.	
Decomposition temperature:	Not determined.	
Auto igniting:	Product is not selfigniting.	
Danger of explosion:	Product does not present an explosion hazard.	
Explosion limits:		
Lower:	Not determined.	
Upper:	Not determined.	
VOC Content (max):	Not determined.	
Vapor pressure:	Not determined.	
Density: (~) at 20 °C (68 °F)	1.1 g/cm ³ (9.18 lbs/gal)	
Relative density	Not determined.	
Vapour density	Not determined.	
Evaporation rate	Not determined.	
Solubility in / Miscibility with		
Water:	Not miscible or difficult to mix.	
	Not miscible or difficult to mix.	
Partition coefficient (n-octanol/wa	ter): Not determined.	
Viscosity:		
Dynamic:	Not determined.	
Kinematic:	Not determined.	
Molecular weight	Not applicable.	
Other information	No further relevant information available.	

10 Stability and reactivity

Thermal decomposition: No decomposition if used according to specifications.

Incompatible materials: No further relevant information available.

Hazardous decomposition products:

Carbon monoxide and carbon dioxide

Other potentially hazardous products may also be formed.

Additional information: See section 7 for information on handling, storage and conditions to be avoided.

USGHS

(Cont. from page 5)

Version Number 1.0

Reviewed on 03/25/2015

Trade name: Bituthene Liquid Membrane Part A

11 Toxicological information

Acute toxicity:

Primary irritant effect:

on the skin: No irritant effect.

on the eye: No irritating effect.

Additional toxicological information: Carcinogenic.

Carcinogenic categories

Carcinog	enic categories	
	ternational Agency for Research on Cancer) Human Carcinogenicity: Positive, Group 2A- Probable, Group 2B- Possible, Group 3- Not Classifiable	
69012-64-	2 Silica, fume	3
8052-42-	4 Asphalt	2B
64742-04-	7 Extracts (petroleum), heavy paraffinic distillate solvent	1
	Polycyclic Aromatic Hydrocarbons	2A
K-Know	ional Toxicology Program) 1 to be carcinogenic, R–May reasonably be anticipated to be carcinogenic	
None of the	e ingredients is listed.	
OSHA-C	a (Occupational Safety & Health Administration)	
None of the	e ingredients is listed.	

12 Ecological information

Aquatic toxicity:

64742-04-7 Extracts (petroleum), heavy paraffinic distillate solvent

LC/EC/IC50 (static) 18.8 mg/l (algae) (OECD guideline 201)

Persistence and degradability No further relevant information available.

Behavior in environmental systems:

Bioaccumulative potential No further relevant information available.

Additional ecological information:

General notes: Not known to be hazardous to water.

13 Disposal considerations

Waste treatment methods Comply with Federal, State and local regulations.

Recommendation:



Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

(Cont. on page 7)

Safety Data Sheet Version Number 1.0

Printing date 03/25/2015

*

Trade name: Bituthene Liquid Membrane Part A

Uncleaned packagings:

Recommendation: Disposal must be made according to official regulations.

14 Transport information	
UN-Number DOT, ADR, ADN, IMDG, IATA	Not applicable.
UN proper shipping name DOT, ADR, ADN, IMDG, IATA	Not applicable.
Transport hazard class(es)	
DOT, ADR, ADN, IMDG, IATA Class	Not applicable.
Packing group DOT, ADR, IMDG, IATA	Not applicable.
Environmental hazards: Marine pollutant:	No
Special precautions for user	•Not applicable.
Transport/Additional inform	mation:
DOT Remarks:	Not Regulated.
UN "Model Regulation":	-

15 Regulatory information

Section 302/304 (extremely hazardou	is substances):
None of the ingredients is listed.	
Section 313 Reportable Ingredients ((Chemicals present below reporting threshold are exempt):
None of the ingredients is listed.	
SARA Section 312/Tier I & II Hazar	rd Categories:
Health Immediate (acute)	Yes
Health Delayed (chronic)	Yes
Flammable	No
Reactive	No
Pressure	No
North America Chemical Inventory	Status
TSCA (Toxic Substances Control Ac	t - United States):
All ingredients are listed or exempt from	om listing unless otherwise noted below.
CEPA (Canadian DSL):	
All ingredients are listed or exempt from	om listing unless otherwise noted below.
Right to Know Ingredient Disclosure	9
69012-64-2 Silica, fume	
69102-90-5 1,3-Butadiene, homopoly	mer, hydroxy-terminated
25791-96-2 Poly[oxy(methyl-1,2-etha	nediyl)], .alpha.,.alpha.',.alpha."-1,2,3-propanetriyltris[.omegahydroxy-
	(Cont. on pa

(Cont. from page 6)

Version Number 1.0

Reviewed on 03/25/2015

Trade name: Bituthene Liquid Membrane Part A

	from page 7)
8001-78-3 Castor oil, hydrogenated	
1332-58-7 Natural aluminosilicate (Kaolin)	
California Proposition 65	
Chemicals known to cause cancer:	
Extracts (petroleum), heavy paraffinic distillate solvent	
Polycyclic Aromatic Hydrocarbons	
Quartz (SiO2)	
4-vinylcyclohexene	
1,3-Butadiene	
Chemicals known to cause reproductive toxicity for females:	
100-40-3 4-vinylcyclohexene	
106-99-0 1,3-Butadiene	
Chemicals known to cause reproductive toxicity for males:	
106-99-0 1,3-Butadiene	
Chemicals known to cause developmental toxicity:	
106-99-0 1,3-Butadiene	
Carcinogenicity Categories	
EPA (Environmental Protection Agency)	
None of the ingredients is listed.	
TLV-ACGIH (THE American Conference of Governmental Industrial Hygienists) Human Carcinogen - A1 Confirmed, A2 Suspected, A3 Unknown Relevance, A4 Not Classifiable	
Asphalt	A4
Natural aluminosilicate (Kaolin)	A4
NIOSH-Cancer (National Institute for Occupational Safety and Health)	
8052-42-4 Asphalt	
Volatile Organic Compounds (VOC) reported per the Emission Standards. (gr/L)10 gr/L (as applied)Information about limitation of use:Workers are not allowed to be exposed to the hazardous carcinogenic materials contained in this preparation.	

Exceptions can be made by the authorities in certain cases.

16 Other information

"The data included herein are presented in accordance with various environment, health and safety regulations. It is the responsibility of a recipient of the data to remain currently informed on chemical hazard information, to design and update its own program and to comply with all national, federal, state and local laws and regulations applicable to safety, occupational health, right-to-know and environmental protection."

Department issuing SDS:

Other Information:

There is sufficient information to conclude that the relative risk of lung cancer is increased in persons with silicosis. Therefore preventing the onset of silicosis will also reduce the cancer risk. **Date of preparation / last revision** 03/25/2015 / -

The first date of preparation 03/03/2015

Number of revision times and the latest revision date 1.0 / 03/25/2015

USGHS =