

SECTION 1: IDENTIFICATION

Product Identifier

Product Form: Mixture
Product Name: Intelliwrap LVP
Product Code: AWB-UAPWB5

Intended Use of the Product

Waterbased air barrier product. For professional use only.

Name, Address, and Telephone

Supplier

IMETCO
4648 South Old Peachtree Rd.
Norcross, GA 30071
T-770-908-1030
F-678-805-4198
www.imetco.com

Emergency Telephone Number

Emergency Number: 1-800-262-8200 (CHEMTREC)

SECTION 2: HAZARDS IDENTIFICATION

Classification of the Substance or Mixture

Classification (GHS-US)

Skin Irrit. 2	H315
Eye Irrit. 2A	H319
STOT SE 3	H335
STOT RE 2	H373

Label Elements

GHS-US Labeling

Hazard Pictograms (GHS-US) :



Signal Word (GHS-US) : Warning

Hazard Statements (GHS-US) :

- H315 – Causes skin irritation
- H319 – Causes serious eye irritation
- H315 – Causes skin irritation
- H335 – May cause respiratory irritation
- H373 – May cause damage to internal organs (kidneys) through prolonged or repeated exposure (oral)

Precautionary Statements (GHS-US) :

- P261 Avoid breathing mist, spray, vapors
- P264 – Wash hands, forearms, and other exposed areas thoroughly after handling
- P271 – Use only outdoors or in a well-ventilated area
- P280 – Wear protective gloves/protective clothing/eye protection/face protection
- P302+P352 – IF ON SKIN: Wash with plenty of soap and water
- P312 – Call a POISON CENTER/doctor/physician if you feel unwell
- P321 – Specific treatment (see Section 4)
- P332+P313 – If skin irritation occurs: Get medical advice/attention
- P337+P313 – If eye irritation persists: Get medical advice/attention
- P362 – Take off contaminated clothing and wash before reuse
- P403+P233 – Store in a well-ventilated place. Keep container tightly closed
- P405 – Store locked up
- P501 – Dispose of contents/container according to local, regional, national, and international regulations

P405 – Store locked up
P501 – Dispose of contents/container according to local, regional, national, and international regulations

Other Hazards

Other Hazards Not Contributing to the Classification: Not available

Unknown Acute Toxicity (GHS-US)

No data available

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

Substance

Not available

Mixture

Name	Product identifier	% (w/w)	Classification (GHS-US)
Calcium carbonate	(CAS No) 471-34-1	40 – 50	Skin Irrit. 2, H315 Eye Irrit. 2B, H320 STOT SE 3, H335
Acrylic polymer solution		20 - 40	Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Water	(CAS No) 7732-18-5	14 - 16	
Cellulose, 2-hydroxyethyl ether	(CAS No) 9004-62-0	5 – 10	Comb. Dust Skin Irrit. 2, H315 Eye Irrit. 2A, H319 STOT SE 3, H335
Propylene glycol	(CAS No) 57-55-6	1 – 1.5	

Full text of H-Phrases: See Section 16

SECTION 4: FIRST AID MEASURES

Description of First Aid Measures

First-aid Measures General: Never give anything by mouth to an unconscious person. If you feel, seek medical advice (show the label where possible).

First-aid Measures After Inhalation: When symptoms occur: go into open air and ventilate suspected area. Remove to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER/doctor/physician if you feel unwell.

First-aid Measures After Skin Contact: Wash with warm soapy water until clean. Area may become irritated if an allergy to the acrylic polymer exists.

First-aid Measures After Eye Contact: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

First-aid Measures After Ingestion: If swallowed, do NOT induce vomiting.

Most Important Symptoms and Effects, Both Acute and Delayed

General: Irritation to eyes, skin, and respiratory tract. Causes damage to organs (kidneys) (Oral).

Symptoms/Injuries After Inhalation: May cause respiratory irritation. May cause drowsiness or dizziness.

Symptoms/Injuries After Skin Contact: May cause skin irritation.

Symptoms/Injuries After Eye Contact: Causes serious eye irritation.

Symptoms/Injuries After Ingestion: Ingestion may cause nausea, vomiting, and diarrhea.

Chronic Symptoms: Causes damage to organs though prolonged or repeated exposure.

Indication of Any Immediate Medical Attention and Special Treatment Needed

If medical advice is needed, have product container or label at hand.

SECTION 5: FIRE-FIGHTING MEASURES

Extinguishing Media

Suitable Extinguishing Media: Carbon dioxide, dry chemical, foam, water spray, fog.

Unsuitable Extinguishing Media: Do not use heavy water stream. Use of heavy stream of water may spread fire.

Special Hazards Arising From the Substance or Mixture

Fire Hazard: Not considered flammable but may burn at high temperatures.
Explosion Hazard: Product is not explosive.
Reactivity: Hazardous reactions will not occur under normal conditions.

Advice for Firefighters

Precautionary Measures Fire: Not available
Firefighting Instructions: Exercise caution when fighting any chemical fire.
Protection During Firefighting: Do not enter fire area without proper protective equipment, including respiratory protection.
Hazardous Combustion Products: Carbon oxides (CO, CO₂).

Reference to Other Sections

Refer to section 9 for flammability properties.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Personal Precautions, Protective Equipment and Emergency Procedures

General Measures: handle in accordance with good industrial hygiene and safety practice.

For Non-emergency Personnel

Protective Equipment: Use appropriate personal protection equipment (PPE).
Emergency Procedures: Evacuate unnecessary personnel.

For Emergency Responders

Protective Equipment: Equip cleanup crew with proper protection.
Emergency Procedures: Ventilate area.

Environmental Precautions

Prevent entry to sewers and public waters.

Methods and Material for Containment and Cleaning Up

For Containment: Contain with dikes or absorbents to prevent migration and entry into sewers or streams. Absorb and/or contain spill with inert material.

Methods for Cleaning Up: Clear up spills immediately and dispose of waste safely.

Reference to Other Sections

See Heading 8, Exposure Controls and Personal Protection.

SECTION 7: HANDLING AND STORAGE

Precautions for Safe Handling

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures. Wash hands and other exposed areas with mild soap and water before eating, drinking, or smoking and when leaving work.

Conditions for Safe Storage, Including Any Incompatibilities

Storage Conditions: Store in a well-ventilated place. Keep container tightly closed. Store locked up. Do not freeze.

Incompatible Materials: Strong acids. Strong bases. Strong oxidizers.

Storage Area: Store locked up. Store in a well-ventilated place. Keep cool.

Special Rules on Packaging: Keep only in original container.

Specific End Use(s)

Urethane roof coating. For professional use only.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

Control Parameters

Calcium Carbonate (471-34-1)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	5 mg/m ³

Propylene Glycol (57-55-6)		
USA OSHA	OSHA PEL (TWA) (mg/m ³)	10 mg/m ³

Exposure Controls

Appropriate Engineering Controls: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure.

Personal Protective Equipment: Gloves. Protective goggles.



Hand Protection: Wear chemically resistant materials and fabrics.

Eye Protection: Chemical goggles or safety glasses. Face shield.

Skin and Body Protection: Wear suitable protective clothing.

Respiratory Protection: If exposure limits are exceeded or irritation is experienced, NIOSH approved respiratory protection should be worn.

Thermal Hazard Protection: Wear suitable protective clothing.

Environmental Exposure Controls: Do not allow the product to be released into the environment.

Consumer Exposure Controls: Do not eat, drink, or smoke during use.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Grey
Odor	: Slight
Odor Threshold	: Not available
pH	: Not available
Relative Evaporation Rate (butyl acetate = 1)	: Not available
Melting Point	: Not available
Freezing Point	: Not available
Boiling Point	: 100°C (212°F)
Flash Point	: Not available
Auto-ignition Temperature	: Not available
Decomposition Temperature	: Not available
Flammability (solid, gas)	: Not available
Lower Flammable Limit	: Not available
Upper Flammable Limit	: Not available
Vapor Pressure	: Not available
Relative Vapor Density at 68°F (20°C)	: Not available
Relative Density	: 12.4 lb/gal
Specific Gravity	: 1.48
Solubility	: Not available
Partition coefficient: n-octanol/water	: Not available
Viscosity (Brookfield RV6, 20 RPM, 75°F)	: Not available
Explosion Data – Sensitivity to Mechanical Impact	: Not available
Explosion Data – Sensitivity to Static Discharge	: Not available
Volatile Organic Compounds	: < 50 g/L

SECTION 10: STABILITY AND REACTIVITY

Reactivity: Hazardous reactions will not occur under normal conditions.

Chemical Stability: Stable at standard temperature and pressure.

Possibility of Hazardous Reactions: None under normal processing.

Conditions to Avoid: Temperatures below zero.

Incompatible Materials: No materials to be especially mentioned.

Hazardous Decomposition Products: None under normal use.

SECTION 11: TOXICOLOGICAL INFORMATION

Information On Toxicological Effects - Product

Acute Toxicity: Not classified.

LD50 and LC50 Data: Not available.

Skin Corrosion/Irritation: Causes skin irritation.

Serious Eye Damage: Causes serious eye irritation.

Respiratory or Skin Sensitization: Not classified.

Germ Cell Mutagenicity: Not classified.

Teratogenicity: Not available.

Carcinogenicity: Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Reproductive Toxicity: May damage fertility or the unborn child.

Aspiration Hazard: Not classified.

Specific Target Organ Toxicity (Single Exposure): Not classified.

Symptoms/Injuries After Inhalation: May cause respiratory irritation. May cause drowsiness or dizziness.

Symptoms/Injuries After Skin Contact: Causes skin irritation.
Symptoms/Injuries After Eye Contact: Causes serious eye irritation.
Symptoms/Injuries After Ingestion: Ingestion may cause nausea, vomiting, and diarrhea.
Chronic Symptoms: Causes damage to organs through prolonged or repeated exposure.

Information on Toxicological Effects – Ingredient(s)

LD50 and LC50 Data

Calcium Carbonate (471-34-1)	
LD50 Oral Rat	6450 mg/kg

Acrylic Polymer Solution	
LD50 Oral Rat	> 5000 mg/kg
LD50 Dermal Rabbit	> 5000 mg/kg

Propylene glycol (57-55-6)	
LD50 Oral Rat	20000 mg/kg

SECTION 12: ECOLOGICAL INFORMATION

Toxicity - Ingredients

Propylene glycol (57-55-6)	
LC50 Fish 1	52930 mg/L (Exposure time: 96 h – Species: Pimephales promelas)
EC50 Daphnia 1	10000 mg/L (Exposure time: 48 h – Species: Daphnia magna)

Persistence and Degradability

Not established

Bioaccumulative Potential – Product

Not established

Bioaccumulative Potential – Ingredients

Mobility in Soil

No additional information available

Other Adverse Effects

Other Information: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

Waste Disposal Recommendations: Dispose of waste material in accordance with all local, regional, national, and international regulations.

SECTION 14: TRANSPORT INFORMATION

In Accordance with DOT – Not regulated for transport

In Accordance with IMDG – Not regulated for transport

In Accordance with IATA – Not regulated for transport

In Accordance with TDG – Not regulated for transport

SECTION 15: REGULATORY INFORMATION

US Federal Regulations

Calcium carbonate (471-34-1)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

Acrylic polymer solution	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

Propylene glycol (57-55-6)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

Cellulose, 2-hydroxyethyl ether (9004-62-0)	
Listed on the United States TSCA (Toxic Substances Control Act) Inventory	

US State Regulations

Propylene glycol (57-55-6)	
RTK – U.S. – New Jersey – Right To Know Hazardous Substance List	

RTK – U.S. – Pennsylvania – RTK (Right To Know) List

Canadian Regulations



Calcium carbonate (471-34-1)

Listed on the Canadian DSL (Domestic Substances List) Inventory

WHMIS Classification	Class D Division 2 Subdivision B – Toxic material causing other toxic effects.
----------------------	--------------------------------------------------------------------------------

Acrylic Polymer Solution

Listed on the Canadian DSL (Domestic Substances List) Inventory

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	-----------------------------------------------------------------

Propylene glycol (57-55-6)

WHMIS Classification	Uncontrolled product according to WHMIS classification criteria
----------------------	-----------------------------------------------------------------

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the SDS contains all of the information required by CPR.

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

- Revision date** : 7/13/2016
- Other Information** : This document has been prepared in accordance with the SDS requirements of the OSHA Hazard Communication Standard 29 CFR 1910.1200.

Party Responsible for the Preparation of This Document

IMETCO.
 4648 South Old Peachtree Rd.
 Norcross, GA 30071
 T-770-908-1030

This information is based on our knowledge as of the Revision Date and is intended to describe the product only for the purposes of health, safety, and environmental requirements as of the Revision Date. It should not therefore be construed as guaranteeing any specific property of the product nor as providing any warranty, expressed or implied. The user assumes all responsibility, liability, risk of loss, damage, or expense arising out of, or in any way connected with, the handling, storage, use, or disposal of the product.

North America GHS US 2016 & WHMIS