



**SCS9000.02 12C-Crtrg(1.0lbs-0.454kg)
ALKOXY SEALANT (white)**

1. CHEMICAL PRODUCT AND COMPANY IDENTIFICATION

Manufactured By: Waterford Plant
260 Hudson River Rd
Waterford NY 12188

Revised: 12/28/2009
Preparer: PRODUCT STEWARDSHIP COMPLIANCE AND STANDARDS
CHEMTREC 1-800-424-9300

Chemical Family/Use: Sealant
Formula: Mixture

HMIS

Flammability: 1 Reactivity: 0 Health: 1

NFPA

Flammability: 1 Reactivity: 0 Health: 1

2. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW

CAUTION! May cause skin, eye, and respiratory tract irritation. Attention: Not for injection into humans.

Form: paste **Color:** white **Odor:** sweet

POTENTIAL HEALTH EFFECTS

INGESTION

May cause stomach discomfort. Not an anticipated route of exposure.

SKIN

Uncured product contact will irritate lips, gums and tongue. Skin irritation is possible after contact with the uncured product.

INHALATION

May cause irritation of the respiratory tract. Applies in uncured state.

EYES

Eye irritation is possible after contact with the uncured product.

MEDICAL CONDITIONS AGGRAVATED

None known.

SUBCHRONIC (TARGET ORGAN)

None known.

CHRONIC EFFECTS / CARCINOGENICITY

This product or one of its ingredients present at 0.1% or more is NOT listed as a carcinogen or



**SCS9000.02 12C-Crtrg(1.0lbs-0.454kg)
ALKOXY SEALANT (white)**

suspected carcinogen by NTP, IARC, or OSHA.

ROUTES OF EXPOSURE

Eyes; dermal

3. COMPOSITION/INFORMATION ON INGREDIENTS

<u>PRODUCT COMPOSITION</u>	<u>CAS REG NO.</u>	<u>WGT. %</u>
<u>A. HAZARDOUS</u>		
Methyltrimethoxysilane	1185-55-3	1 - 5 %
<u>B. NON-HAZARDOUS</u>		
Dimethylpolysiloxane	70131-67-8	30 - 60 %
CALCIUM CARBONATE	1317-65-3	30 - 60 %
Polydimethylsiloxane	63148-62-9	5 - 10 %
Treated Filler	68611-44-9	1 - 5 %
Titanium Dioxide	13463-67-7	1 - 5 %

4. FIRST AID MEASURES

INGESTION

Do not induce vomiting. If victim is conscious, give 1-3 glasses of water to drink. Never give anything by mouth to an unconscious person. Get medical attention if irritation persists.

SKIN

To clean from skin, remove completely with a dry cloth or paper towel, before washing with detergent and water. If skin irritation persists, call a physician.

INHALATION

If inhaled, remove to fresh air. If not breathing give artificial respiration using a barrier device. If breathing is difficult give oxygen. Get medical attention.

EYES

In case of contact, immediately flush eyes with plenty of water for at least 15 minutes and get medical attention if irritation persists.

NOTE TO PHYSICIAN

Treatment is symptomatic and supportive.



**SCS9000.02 12C-Crtrg(1.0lbs-0.454kg)
ALKOXY SEALANT (white)**

5. FIRE-FIGHTING MEASURES

FLASH POINT: > 93.3 °C; 200 °F
METHOD: estimated
FLAMMABLE LIMITS IN AIR - LOWER (%): no data available
FLAMMABLE LIMITS IN AIR - UPPER (%): no data available

SENSITIVITY TO MECHANICAL IMPACT: No

SENSITIVITY TO STATIC DISCHARGE
Sensitivity to static discharge is not expected.

EXTINGUISHING MEDIA
All standard extinguishing agents are suitable.

SPECIAL FIRE FIGHTING PROCEDURES
Firefighters must wear NIOSH/MSHA approved positive pressure self-contained breathing apparatus with full face mask and full protective clothing.

6. ACCIDENTAL RELEASE MEASURES

ACTION TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED
Wipe, scrape or soak up in an inert material and put in a container for disposal. Wear proper protective equipment as specified in the protective equipment section. Increase area ventilation.

7. HANDLING AND STORAGE

PRECAUTIONS TO BE TAKEN IN HANDLING AND STORAGE
Keep container closed when not in use. Avoid contact with skin and eyes. Remove contact lenses before using sealant. Do not handle lenses until all sealant has been cleaned from the fingertips, nails and cuticles. Residual sealant may remain on fingers for several days and transfer to lenses and cause severe eye irritation. Product releases methanol during application and curing. Keep away from children.

STORAGE
Store away from heat, sources of ignition, and incompatibles. Keep container tightly closed.



**SCS9000.02 12C-Crtrg(1.0lbs-0.454kg)
ALKOXY SEALANT (white)**

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS

Eyewash stations; Showers; Ventilation and other forms of engineering controls are preferred for controlling exposures. Respiratory protection may be needed for non-routine or emergency situations.

RESPIRATORY PROTECTION

If exposure limits are exceeded or respiratory irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Supplied air respirators may be required for non-routine or emergency situations. Respiratory protection must be provided in accordance with OSHA regulations (see 29CFR 1910.134).

PROTECTIVE GLOVES

Rubber gloves

EYE AND FACE PROTECTION

Safety glasses

OTHER PROTECTIVE EQUIPMENT

Wear suitable protective clothing and eye/face protection.

Exposure Guidelines

Component	CAS RN	Source	Value
-----------	--------	--------	-------

Absence of values indicates none found

PEL - OSHA Permissible Exposure Limit; TLV - ACGIH Threshold Limit Value; TWA - Time Weighted Average; INTL REL - Internal Recommended Exposure Limit

OSHA revoked the Final Rule Limits of January 19, 1989 in response to the 11th Circuit Court of Appeals decision (AFL-CIO v. OSHA) effective June 30, 1993. See 29 CFR 1910.1000 (58 FR 35338).

9. PHYSICAL AND CHEMICAL PROPERTIES

VAPOR PRESSURE (20 C) (MM HG):	no data available
VAPOR DENSITY (AIR=1):	negligible
PHYSICAL STATE:	paste
ODOR:	sweet
COLOR:	white
EVAPORATION RATE (BUTYL ACETATE=1):	< 1
SPECIFIC GRAVITY (WATER=1):	ca. 1.4
DENSITY:	ca. 1.4 g/cm ³
ACID / ALKALINITY (MEQ/G):	Unknown
SOLUBILITY IN WATER (20 C):	INSOLUBLE
SOLUBILITY IN ORGANIC SOLVENT (STATE SOLVENT):	insoluble
VOC EXCL. H2O & EXEMPTS (G/L):	37 g/l



**SCS9000.02 12C-Crtrg(1.0lbs-0.454kg)
ALKOXY SEALANT (white)**

10. STABILITY AND REACTIVITY

STABILITY

Stable

HAZARDOUS POLYMERIZATION

Will not occur.

HAZARDOUS THERMAL DECOMPOSITION / COMBUSTION PRODUCTS

Carbon dioxide (CO₂); Carbon monoxide; Methanol; Silicon dioxide.; formaldehyde; This product contains methylpolysiloxanes which can generate formaldehyde at approximately 300 degrees Fahrenheit (150°C) and above, in atmospheres which contain oxygen. Formaldehyde is a skin and respiratory sensitizer, eye and throat irritant, acute toxicant, and potential cancer hazard. A MSDS for formaldehyde is available from Momentive.

INCOMPATIBILITY (MATERIALS TO AVOID)

None known.

CONDITIONS TO AVOID

None known.

11. TOXICOLOGICAL INFORMATION

ACUTE ORAL

Remarks: Unknown

ACUTE DERMAL

Remarks: Unknown

ACUTE INHALATION

Remarks: no data available

OTHER

None.

SENSITIZATION

no data available

SKIN IRRITATION

no data available

EYE IRRITATION

no data available



**SCS9000.02 12C-Crtrg(1.0lbs-0.454kg)
ALKOXY SEALANT (white)**

MUTAGENICITY

Unknown

12. ECOLOGICAL INFORMATION

ECOTOXICITY

no data available

DISTRIBUTION

no data available

CHEMICAL FATE

no data available

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD

Disposal should be made in accordance with federal, state and local regulations.

14. TRANSPORT INFORMATION

Further Information:

This product is not regarded as dangerous goods according to the national and international regulations on the transport of dangerous goods.

15. REGULATORY INFORMATION

Inventories

Korea Existing Chemicals Inventory (KECI)	y (positive listing)
China Inventory of Existing Chemical Substances	y (positive listing)
Australia Inventory of Chemical Substances (AICS)	y (positive listing)
Philippines Inventory of Chemicals and Chemical Substances (PICCS)	y (positive listing)
EU list of existing chemical substances	y (positive listing)



**SCS9000.02 12C-Crtrg(1.0lbs-0.454kg)
ALKOXY SEALANT (white)**

Canada NDSL Inventory n (Negative listing)
Japan Inventory of Existing & t (temporary special
New Chemical Substances case)
(ENCS)
Canada DSL Inventory y (positive listing)
TSCA list y (positive listing) On TSCA Inventory
For inventories that are marked as quantity restricted or special cases, please contact Momentive.

US Regulatory Information

SARA (311,312) HAZARD CLASS
Acute Health Hazard

SARA (313) CHEMICALS

CALIFORNIA PROPOSITION 65

Warning! This product contains a chemical known to the State of California to cause cancer, birth defects or other reproductive harm.
7439-92-1, Lead.

Canadian Regulatory Information

WHMIS HAZARD CLASS
- Non-controlled.

Other

SCHDLE B/HTSUS: 3214.10.00.10 Mastic based on rubber

16. OTHER INFORMATION

OTHER

These data are offered in good faith as typical values and not as product specifications. No warranty, either expressed or implied, is made. The recommended industrial hygiene and safe handling procedures are believed to be generally applicable. However, each user should review these recommendations in the specific context of the intended use and determine whether they are appropriate., C = ceiling limit NEGL = negligible EST = estimated NF = none found
NA = not applicable UNKN = unknown NE = none established REC = recommended ND = none determined V = recommended by vendor SKN = skin TS = trade secret R = recommended MST = mist NT = not tested STEL = short term exposure limit ppm = parts per million ppb = parts per billion By-product= reaction by-product, TSCA inventory status not required under 40 CFR part 720.30(h-2).