

Material Safety Data Sheet

Revision Date: 06-18-2012
Product Code: FC7530-00

I. PRODUCT AND COMPANY IDENTIFICATION

Product Name: FC ALIPHATIC URETHANE TOP COAT NEUTRAL BASE
Product Code: FC7530-00
Document ID: MFC7530-00
Company: NEOGARD® - a Division of JONES-BLAIR® Company
2728 Empire Central
Dallas, TX 75235
1-214-353-1600

Revision Number: 3
Prior Version Date: 05-28-2009
Chemical Family: Urethane Floor Coating
Intended use: Industrial Maintenance Floor TopCoat Urethane
Emergency Contact: ChemTrec Center
Emergency Phone: 1-800-424-9300
International: 703-527-3887

II. HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: **DANGER!**
Causes skin irritation.
Causes eye irritation.
Vapor and spray mist harmful. Causes nose and throat irritation. Overexposure may cause lung damage. May cause allergic skin and respiratory reaction. Effects may be permanent.

Routes of Entry:

- Inhalation
- Ingestion
- Skin contact
- Eye contact

Target Organs Potentially Affected by Exposure:

- Skin
- Respiratory Tract
- Liver
- Kidneys

Medical Conditions Aggravated by Exposure:

- Skin allergies.
- Individuals with lung or breathing problems or prior reaction to isocyanates must not be exposed to vapor or spray mist.
- Respiratory disorders, including but not limited to asthma and bronchitis.
-

Immediate (Acute) Health Effects by Route of Exposure:

Inhalation Toxicity: Vapor harmful. May affect the brain or nervous system causing dizziness, headache or nausea.

Skin Contact: Can cause moderate skin irritation. Sensitizer. Avoid exposure. If sensitized, repeated exposures will result in irritation, reddening, and rashes even for very low exposures. May cause allergic skin reaction.

Skin Absorption: May be harmful if absorbed through skin.

Eye Contact: Can cause severe irritation. Eye contact may result in corneal injury. Symptoms may include discomfort or pain, excess blinking and tear production, with marked redness and swelling of the conjunctiva. Temporary vision impairment (cloudy or blurred vision) is possible.

Ingestion Toxicity: Harmful if swallowed.

Long-Term (Chronic) Health Effects:

Inhalation: Isocyanate vapors or mist at concentrations above the TLV can irritate the mucous membranes in the respiratory tract causing runny nose, sore throat, coughing, chest

Material Safety Data Sheet

Revision Date: 06-18-2012

Product Code: FC7530-00

discomfort, shortness of breath and reduced lung function. Exposure well above the TLV may lead to generally reversible bronchitis, bronchial spasm and pulmonary edema.

Repeated overexposure causes sensitization in some individuals resulting in asthma-like symptoms on subsequent exposures below the TLV.

Persons with preexisting bronchial hyperactivity can respond to concentrations below the TLV with similar symptoms as well as an asthma attack.

NOTICE: Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents may be harmful or fatal.

Skin Contact:

Prolonged contact may cause an allergic skin reaction.

III. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	%	CAS #
Homopolymer of Isophorone Diisocyanate	70 - 90	53880-05-0
ISOPHORONE DIISOCYANATE	1 - 5	4098-71-9
Methyl Piperidene Sebacate Derivative	1 - 5	41556-26-7
Butyl carbitol acetate	0.5 - 1.5	124-17-4
(d)-Limonene	0.5 - 1.5	5989-27-5

IV. FIRST-AID MEASURES

Inhalation:	Remove individual to fresh air after an airborne exposure if any symptoms develop as a precautionary measure. If breathing difficulty persists or occurs later, consult a physician and have MSDS available.
Eyes:	In case of contact, immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention immediately.
Skin Contact:	Wash with soap and water. Remove contaminated clothing and launder. Get medical attention if irritation develops or persists. Thoroughly wash or discard clothing and shoes before reuse.
Ingestion:	If swallowed, do not induce vomiting. Get medical attention immediately.

V. FIRE FIGHTING MEASURES

Extinguishing Media:	Use alcohol foam, carbon dioxide, or water spray when fighting fires involving this material.
Fire and/or Explosion Hazards:	Material may be ignited only if preheated to temperatures above the high flash point, for example in a fire.
Fire Fighting Methods and Protection:	Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment. Do not enter fire area without proper protection including self-contained breathing apparatus and full protective equipment.
Hazardous Combustion Products:	Carbon dioxide, Carbon monoxide, Nitrogen containing gases, Isocyanates, Hydrogen cyanide, Isocyanic Acid, Toxic fumes, Toxic gases, Hydrocarbons

Flash Point (°F/°C):	205 / 96
Lower Flammable/Explosive Limit, % in air:	0.7

VI. ACCIDENTAL RELEASE MEASURES

Personal Precautions and Equipment:	Exposure to the spilled material may be irritating or harmful. Follow personal protective equipment recommendations found in Section VIII of this MSDS. Additional precautions may be necessary based on special circumstances created by the spill including the material spilled, the quantity of the spill, the area in which the spill occurred. Also consider the expertise of employees in the area responding to the spill.
Methods for Clean-up:	Prevent the spread of any spill to minimize harm to human health and

Material Safety Data Sheet

Revision Date: 06-18-2012

Product Code: FC7530-00

the environment if safe to do so. Dike with suitable absorbent material. Gather and store in a sealed container pending disposal.

VII. HANDLING AND STORAGE

Handling Technical Measures and Precautions: Harmful or irritating material. Avoid contacting and avoid breathing the material. Use only in a well ventilated area. As with all chemicals, good industrial hygiene practices should be followed when handling this material. Wash thoroughly after handling. Do not get in eyes, on skin and clothing.

Storage Technical Measures and Conditions: Store in a cool dry place. Keep container(s) closed.

VIII. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures: Use local exhaust ventilation or other engineering controls to minimize exposure. Engineering controls must be designed to meet the OSHA chemical specific standard in 29 CFR 1910.

Respiratory Protection: General or local exhaust ventilation is the preferred means of protection. In cases where ventilation is inadequate, respiratory protection may be required to avoid overexposure. Follow respirator manufacturer's directions for respirator use. For poorly ventilated areas or during spray application use NIOSH approved supplied air respirator unless air monitoring demonstrates vapor/mist levels below applicable limits. When monomeric isocyanate concentrations are below 0.05 ppm (10 times the 8 hour TWA exposure limit), an appropriate combination organic vapor and particulate respirator (NIOSH approved) may be appropriate. An end-of-service-life Indicator (ESLI) or a change schedule is mandatory.

Eye Protection: Wear chemically resistant safety glasses with side shields when handling this product. Wear additional eye protection such as chemical splash goggles and/or face shield when the possibility exists for eye contact with splashing or spraying liquid, or airborne material. Have an eye wash station available.

Skin Protection: Avoid all skin contact by covering as much of the exposed skin area as possible with appropriate clothing to prevent skin contact. Wash hands and other exposed areas with mild soap and water before eating, drinking, and when leaving work. Clothing suitable to prevent skin contact. Wear chemical resistant gloves.

Control Parameters:

Chemical Name	ACGIH TLV-TWA	ACGIH STEL	OSHA PEL-TWA
ISOPHORONE DIISOCYANATE	0.005 ppm (TWA)		

IX. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Liquid

VOC (g/l) (Regulatory, Calculated): 42.14
(Actual, Calculated): 42.14

Viscosity: 3300 - 4300 CPS

Solubility in Water: Negligible; 0-1%

Octanol/Water Partition Coefficient: Not Available

Volatiles, % by Volume (Calculated): 5.33

Volatiles, % by weight (Calculated): 4.17

Density: 8.42 - 8.62 lbs./Gal.

Physical and Chemical Properties are calculated target or range values for single packaged items and do not represent compliance values for multi-component (mixed) systems.

X. STABILITY AND REACTIVITY

Stability: Stable under normal conditions.

Conditions to Avoid: Temperatures above the high flash point of this combustible material in combination with sparks, open flames, or other sources of ignition. Contamination.

Material Safety Data Sheet

Revision Date: 06-18-2012

Product Code: FC7530-00

Materials to Avoid/Chemical Incompatibility: Moisture, Amines, Alcohols, Caustics (bases, alkalis), Oxidizing agents

Polymerization: Contact with moisture, other materials that react with isocyanates or temperatures above 350° F may cause polymerization.

Hazardous Decomposition Products: Carbon dioxide, Carbon monoxide, Nitrogen containing gases, Isocyanates, Hydrogen cyanide, Isocyanic Acid, Toxic fumes, Toxic gases

XI. TOXICOLOGICAL INFORMATION

Component Toxicology Data:

Chemical Name	CAS Number	LD50/LC50
Homopolymer of Isophorone Diisocyanate	53880-05-0	Oral LD50 Rat > 5000 mg/kg Dermal LD50 Rabbit > 2000 mg/kg Inhalation LC50 (4h) Rat > 5018 mg/m ³
ISOPHORONE DIISOCYANATE	4098-71-9	Oral LD50 Rat 5490 mg/kg Dermal LD50 Rabbit 4780 mg/kg Inhalation LC50 (4h) Rat 40 mg/kg
Butyl carbitol acetate	124-17-4	Oral LD50 Rat 6960 - 11960 mg/kg Dermal LD50 Rabbit 5390 - 14500 mg/kg

Carcinogens:

Chemical Name	CAS Number	IARC	NTP	OSHA
Not applicable				

XII. ECOLOGICAL INFORMATION

Toxicity data, if available, are listed below.

XIII. DISPOSAL CONSIDERATIONS

Disposal Methods: Refer to other sections of this MSDS to determine the toxicity and physical characteristics of the material to determine the proper waste identification and disposal in compliance with applicable regulations.

XIV. TRANSPORTATION INFORMATION

This section provides basic shipping classification information and does not contain all regulatory transportation details. Refer to all applicable regulations for domestic, international, air, vessel and ground transportation requirements and restrictions.

DOT Basic Description: Paint, Not-Regulated

XV. REGULATORY INFORMATION

United States Federal Regulations:

TSCA Status All components of this product are either listed on the TSCA Inventory; or, are not subject to the inventory notification requirements.

SARA EHS Chemicals	CAS #	%
Isophorone diisocyanate	4098-71-9	1 - 5

CERCLA

Not applicable

Material Safety Data Sheet

Revision Date: 06-18-2012

Product Code: FC7530-00

SARA 313

Isophorone diisocyanate	4098-71-9	1 - 5
2-(2-Butoxyethoxy)ethyl acetate	124-17-4	0.5 - 1.5

SARA 311/312

Health (Acute):	Y
Health (chronic):	Y
Fire (Flammable):	N
Pressure:	N
Reactivity:	Y

U. S. State Regulations:

California Prop 65 Chemicals

Cancer

	<u>CAS #</u>	<u>%</u>
Ethyl Benzene	100-41-4	0.01 - 0.1
Benzene	71-43-2	< 1 ppm

Reproductive

Toluene	108-88-3	0.001- 0.01
Benzene	71-43-2	< 1 ppm

Canadian Regulations:

CEPA DSL: The components of this product ARE listed on the Canadian Domestic Substances List.

WHMIS Hazard Class: D2A

XVI. ADDITIONAL INFORMATION

Prepared By: Regulatory Department

Disclaimer: This MSDS has been prepared in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada's Controlled Product Regulations (CPR). To the best of our knowledge the information contained herein is accurate. Determination of safe handling, application and use of this material is the responsibility of the end user. This information is furnished without warranty, expressed or implied.

Print Date: June 18, 2012