

# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

#### MANUFACTURER

ITW Polymers Sealants North America  
12271 Monarch St.  
Garden Grove, CA 92841  
**Product Stewardship:** (714) 898-0025

#### 24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

**COMMENTS:** PACIFIC POLYMERS and Elasto-Poxy are a registered trademarks of Illinois Tool Works, Inc.

### 2. HAZARDS IDENTIFICATION

#### GHS CLASSIFICATIONS

##### Health:

Skin Irritation, Category 2  
Eye Irritation, Category 2A  
Reproductive Toxicity, Category 2  
Target Organ Toxicity (Single exposure), Category 3  
Target Organ Toxicity (Repeated exposure), Category 2  
Aspiration Hazard, Category 1

##### Environmental:

Acute Hazards to the Aquatic Environment, Category 2  
Chronic Hazards to the Aquatic Environment, Category 3

##### Physical:

Flammable Liquids, Category 2

#### GHS LABEL



Flame



Exclamation  
mark



Health  
hazard

**SIGNAL WORD:** DANGER

#### HAZARD STATEMENTS

H225: Highly flammable liquid and vapour.  
H304: May be fatal if swallowed and enters airways.  
H315: Causes skin irritation.  
H319: Causes serious eye irritation.  
H335: May cause respiratory irritation.  
H336: May cause drowsiness or dizziness.  
H361: Suspected of damaging fertility or the unborn child.  
H373: May cause damage to organs through prolonged or repeated exposure.  
H401: Toxic to aquatic life.  
H412: Harmful to aquatic life with long lasting effects.

#### PRECAUTIONARY STATEMENT(S)

##### Prevention:

# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

[201]: Obtain special instructions before use.  
 P202: Do not handle until all safety precautions have been read and understood.  
 P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.  
 P233: Keep container tightly closed.  
 P240: Ground/bond container and receiving equipment.  
 P241: Use explosion-proof electrical/ventilating/lighting equipment.  
 P242: Use only non-sparking tools.  
 P243: Take precautionary measures against static discharge.  
 P260: Do not breathe dust/fume/gas/mist/vapours/spray.  
 P264: Wash hands, forearms, and other exposed areas thoroughly after handling.  
 P271: Use only outdoors or in a well-ventilated area.  
 P272: Contaminated work clothing should not be allowed out of the workplace.  
 P273: Avoid release to the environment.  
 P280: Wear protective gloves/protective clothing/eye protection/face protection.  
 P284: Wear respiratory protection.

### Response:

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.  
 P302+P352: IF ON SKIN: Wash with plenty of soap and water.  
 P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.  
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P312: Call a POISON CENTER or doctor/physician if you feel unwell.  
 P314: Get medical advice/attention if you feel unwell.  
 P321: Specific treatment (see section 4).  
 P331: Do NOT induce vomiting.  
 P332+P313: If skin irritation occurs: Get medical advice/attention.  
 P333+P313: If skin irritation or rash occurs: Get medical advice/attention.  
 P337+P313: If eye irritation persists: Get medical advice/attention.  
 P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.  
 P362: Take off contaminated clothing and wash before reuse.  
 P370+P378: In case of fire: Use appropriate media to extinguish.  
 P391: Collect spillage.

### Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.  
 P403+P235: Store in a well-ventilated place. Keep cool.  
 P405: Store locked up.

### Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

### EMERGENCY OVERVIEW

**IMMEDIATE CONCERNS:** DANGER! Flammable liquid and vapor. Vapor may cause flash fire. Harmful or fatal if swallowed. Harmful if absorbed through the skin. Pulmonary aspiration hazard. After ingestion, may enter lungs and produce damage. High vapor concentrations may cause drowsiness. Can cause eye, skin and respiratory tract irritation.

### POTENTIAL HEALTH EFFECTS

**EYES:** Can cause severe eye irritation and corneal damage.  
**SKIN:** Causes defatting and skin irritation. Can cause dermatitis.

# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

**INGESTION:** Can cause gastrointestinal irritation, nausea and vomiting. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Harmful or fatal if swallowed.

**INHALATION:** May cause nose or throat irritation. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

**ROUTES OF ENTRY:** Eye and Skin Contact, Inhalation and Ingestion

**TARGET ORGAN STATEMENT:** Central Nervous System (CNS)

**IRRITANCY:** Eyes, nose, throat, respiratory tract, and skin irritation.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
p-Chlorobenzotrifluoride	< 25	98-56-6
Xylenes (o-,m-,p- Isomers)	< 7	1330-20-7
Methyl Isobutyl Ketone	< 6	108-10-1

### 4. FIRST AID MEASURES

**EYES:** Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

**SKIN:** Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

**INGESTION:** Do not induce vomiting, keep person warm, quiet and get medical attention immediately. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Aspiration of this material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

#### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**EYES:** Liquid and vapor can severely irritate the eyes depending on type of exposure (splash, vapor) and exposure time.

**SKIN:** Mild to moderate skin irritant.

**INGESTION:** May result in central nervous system (CNS) depression with symptoms such as headaches, nausea, vomiting, diarrhea, dizziness, incoordination and unconsciousness. Aspiration of material into lungs may cause chemical pneumonitis which can be fatal.

**INHALATION:** High vapor concentrations may cause CNS depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion, and unconsciousness.

**ACUTE TOXICITY:** High vapor concentrations may cause central nervous system (CNS) depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion and unconsciousness.

**CHRONIC EFFECTS:** Damage to the nervous system of the extremities, peripheral neuropathy, with symptoms including numbness, tingling and weakness in the toes and fingers, sensory impairment to touch, pain, vibration and temperature, muscular weakness, blurred vision, coldness of extremities, loss of body weight and reflexes, and even paralysis. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

### 5. FIRE FIGHTING MEASURES

# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

**FLAMMABLE CLASS:** Class IC

**GENERAL HAZARD:** Flammable liquid and vapor.

**EXTINGUISHING MEDIA:** Foam, dry chemical, carbon dioxide, water spray or fog.

**HAZARDOUS COMBUSTION PRODUCTS:** Carbon Monoxide, Carbon Dioxide, Aldehydes

**EXPLOSION HAZARDS:** Avoid fire, sparks, static electricity and hot surfaces. Liquid readily evaporates at room/ambient temperature. Vapors are invisible, flammable, heavier than air, and may accumulate in low areas and spread long distances. Distant ignition and flashback are possible.

**FIRE FIGHTING PROCEDURES:** As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

**SENSITIVE TO STATIC DISCHARGE:** Likely to catch fire from near-by spark. Static charge may accumulate by flow or agitation. Grounding and bonding of containers is required.

**SENSITIVITY TO IMPACT:** None known.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon Monoxide and Carbon Dioxide may form when heated to decomposition.

### 6. ACCIDENTAL RELEASE MEASURES

**SMALL SPILL:** Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. After all visible traces, including ignitable vapors, have been removed, thoroughly wet vacuum the area. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up.

**LARGE SPILL:** Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Ventilate the area by natural means or by explosion proof mechanical means (i.e. fans). Know and prepare for spill response before using or handling this product. Eliminate all ignition sources (flames, hot surfaces, portable heaters and sources of electrical, static, or frictional sparks). Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled metal containers for recovery or disposal, or remove with inert absorbent. Use only non-sparking tools and appropriate PPE. Place absorbent diking materials in covered metal containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. Flammable vapors may cause flash fire or ignite explosively. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Containers may be hazardous when empty. Never use welding or cutting torch on or near container. Do not cut, drill, grind, or expose containers to heat, sparks, static electricity or other source of ignition. Explosion may occur causing injury or death.

**HANDLING:** Use adequate ventilation and appropriate respiratory protection to avoid breathing vapors when cover is removed. Ground and bond all equipment when handling flammable solvent-borne material.

**STORAGE:** Keep container closed when not in use. Store in a dry, well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

**STORAGE TEMPERATURE:** 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

**SHELF LIFE:** 1 year from manufacture date

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

#### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m <sup>3</sup>	ppm	mg/m <sup>3</sup>
p-Chlorobenzotrifluoride	<b>TWA</b>	NL [1]	NL [1]	NL [1]	NL [1]
	<b>STEL</b>	NL [1]	NL [1]	NL [1]	NL [1]
Xylenes (o-,m-,p- Isomers)	<b>TWA</b>	100 ppm	435 mg/m <sup>3</sup>	100 ppm	434 mg/m <sup>3</sup>
	<b>STEL</b>	NL [1]	NL [1]	150 ppm	651 mg/m <sup>3</sup>
Methyl Isobutyl Ketone	<b>TWA</b>	100 ppm	410 mg/m <sup>3</sup>	20 ppm [1]	NL [1]
	<b>STEL</b>	NL [1]	NL [1]	75 ppm [1]	NL [1]
<b>Footnotes:</b>					
1. NL = Not Listed					

**ENGINEERING CONTROLS:** Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration.

#### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Wear safety glasses with side shields (or goggles) or a full face respirator.

**SKIN:** Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

**RESPIRATORY:** NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

**PROTECTIVE CLOTHING:** Wear chemical resistant gloves, such as nitrile rubber.

**WORK HYGIENIC PRACTICES:** Use good hygiene practices when handling this material. Wash hands thoroughly after use.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid

**ODOR:** Solvent-like

# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

**ODOR THRESHOLD:** Not Determined  
**COLOR:** Clear to Straw Yellow  
**pH:** Not Determined  
**PERCENT VOLATILE:** 28.0  
**Notes:** by weight  
**FLASHPOINT AND METHOD:** 31.1°C (88°F)  
**FLAMMABLE LIMITS:** 0.9 to 10.5  
**AUTOIGNITION TEMPERATURE:** (932°F)  
**VAPOR PRESSURE:** Not Determined  
**VAPOR DENSITY:** Not Determined  
**BOILING POINT:** Not Determined  
**FREEZING POINT:** Not Determined  
**MELTING POINT:** Not Determined  
**POUR POINT:** Not Determined  
**SOLUBILITY IN WATER:** Slight  
**EVAPORATION RATE:** > 1.0 (n-Butyl Acetate=1)  
**DENSITY:** 9.44 lbs/gal  
**PARTICLE SIZE:** Not Determined  
**SPECIFIC GRAVITY:** 1.132  
**VISCOSITY:** Not Determined  
**MOLECULAR WEIGHT:** Not Determined  
**(VOC):** 65.000 gr/L EPA Method 24 VOC  
**COEFF. OIL/WATER:** Not Determined  
**OXIDIZING PROPERTIES:** Not Determined

### 10. STABILITY AND REACTIVITY

**STABLE:** Yes  
**HAZARDOUS POLYMERIZATION:** No  
**STABILITY:** Stable.  
**POLYMERIZATION:** Product will not undergo polymerization.  
**CONDITIONS TO AVOID:** Avoid fire, sparks, static electricity and hot surfaces.  
**POSSIBILITY OF HAZARDOUS REACTIONS:** None Expected.  
**HAZARDOUS DECOMPOSITION PRODUCTS:** Carbon monoxide and carbon dioxide may form when heated to decomposition.  
**INCOMPATIBLE MATERIALS:** Strong oxidizing agents, strong acids and strong bases.

### 11. TOXICOLOGICAL INFORMATION

**ACUTE**

# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

Chemical Name	ORAL LD <sub>50</sub> (rat)	DERMAL LD <sub>50</sub> (rabbit)	INHALATION LC <sub>50</sub> (rat)
p-Chlorobenzotrifluoride	> 6800 mg/kg	> 2700 mg/kg	4479 ppm (4-hr dose)
Xylenes (o-,m-,p- Isomers)	4300 mg/kg	2000 mg/kg	26800 ppm
Methyl Isobutyl Ketone	2080 mg/kg (rats)	> 10 ml/kg (rabbit)	2000 to 4000 ppm (4-hr dose - rat)

### CARCINOGENICITY

Chemical Name	IARC Status
Xylenes (o-,m-,p- Isomers)	3

**IRRITATION:** Eyes, nose, throat, respiratory tract irritation.

### 12. ECOLOGICAL INFORMATION

**ENVIRONMENTAL DATA:** This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

**ECOTOXICOLOGICAL INFORMATION:** Contains components that are potentially toxic to freshwater and saltwater ecosystems.

**BIOACCUMULATION/ACCUMULATION:** Contains components with the potential to bio-accumulate.

### 13. DISPOSAL CONSIDERATIONS

**DISPOSAL METHOD:** Dispose of in accordance with all local, state and federal regulations.

### 14. TRANSPORT INFORMATION

#### DOT (DEPARTMENT OF TRANSPORTATION)

**PROPER SHIPPING NAME:** Resin Solution

**PRIMARY HAZARD CLASS/DIVISION:** 3

**UN/NA NUMBER:** 1866

**PACKING GROUP:** III

**LABEL:** Flammable Liquid

**MARINE POLLUTANT #1:** None

**OTHER SHIPPING INFORMATION:** (Methyl Isobutyl Ketone, Xylene)

#### AIR (ICAO/IATA)

**SHIPPING NAME:** Resin Solution

**TECHNICAL NAME:** (Methyl Isobutyl Ketone, Xylene)

**UN/NA NUMBER:** 1866

**PRIMARY HAZARD CLASS/DIVISION:** 3

**PACKING GROUP:** III

**LABEL:** FLAMMABLE LIQUID

# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

**VESSEL (IMO/IMDG)**

**SHIPPING NAME:** Resin Solution  
**TECHNICAL NAME:** (Methyl Isobutyl Ketone, Xylene)  
**UN/NA NUMBER:** 1866  
**PRIMARY HAZARD CLASS/DIVISION:** 3  
**PACKING GROUP:** III  
**LABEL:** FLAMMABLE LIQUID

### 15. REGULATORY INFORMATION

**UNITED STATES**
**DOT LABEL SYMBOL AND HAZARD CLASSIFICATION**


Flammable  
Liquid

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**FIRE:** Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt.%	CAS
Xylenes (o-,m-,p- Isomers)	< 7	1330-20-7
Methyl Isobutyl Ketone	< 6	108-10-1

**CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)**

Chemical Name	Wt.%	CERCLA RQ
Xylenes (o-,m-,p- Isomers)	< 7	100
Methyl Isobutyl Ketone	< 6	5,000

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS	TSCA SECTION
p-Chlorobenzotrifluoride	98-56-6	
Xylenes (o-,m-,p- Isomers)	1330-20-7	8a, 8d, 12b,
Methyl Isobutyl Ketone	108-10-1	

**CLEAN AIR ACT**

Chemical Name	Wt.%	CAS
Xylenes (o-,m-,p- Isomers)	< 7	1330-20-7



# SAFETY DATA SHEET

Date Issued : 3/27/2015  
MSDS No : PP EPP-VOC A

## PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component A

### STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
p-Chlorobenzotrifluoride	New Jersey Right to Know List Pennsylvania Right to Know List
Xylenes (o-,m-,p- Isomers)	New Jersey Right to Know List Pennsylvania Right to Know List Massachusetts Toxic Use Reduction Act (TURA) Reportable Chemical Illinois Right to Know List Minnesota Right to Know List Rhode Island Right to Know List

### CANADA

#### WHMIS HAZARD SYMBOL AND CLASSIFICATION



Flammable  
Liquid



Toxic


### 16. OTHER INFORMATION

**INFORMATION CONTACT:** (714) 898-0025

#### HMIS RATING

<b>HEALTH</b>	*	<b>2</b>
<b>FLAMMABILITY</b>		<b>3</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>B</b>

#### NFPA CODES



**GENERAL STATEMENTS:** Keep out of reach of children  
For professional or industrial use only

**MANUFACTURER DISCLAIMER:** This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.