

SAFETY DATA SHEET

Date Issued : 3/31/2015
MSDS No : PP EPP-VOC B

PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

MANUFACTURER

ITW Polymers Sealants North America
12271 Monarch St.
Garden Grove, CA 92841
Product Stewardship: (714) 898-0025

24 HR. EMERGENCY TELEPHONE NUMBERS

CHEMTREC (US Transportation): (800) 424-9300

COMMENTS: PACIFIC POLYMERS and Elasto-Poxy are a registered trademarks of Illinois Tool Works, Inc.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Skin Corrosion, Category 1B
Serious Eye Damage, Category 1
Target Organ Toxicity (Single exposure), Category 3
Skin Sensitization, Category 1
Acute Toxicity (Oral), Category 4
Acute Toxicity (Inhalation), Category 1
Acute Toxicity (Dermal), Category 4

GHS LABEL



Exclamation
mark



Corrosion



Health
hazard

SIGNAL WORD: DANGER

HAZARD STATEMENTS

H335: May cause respiratory irritation.
H314: Causes severe skin burns and eye damage.
H318: Causes serious eye damage.
H317: May cause an allergic skin reaction.
H302: Harmful if swallowed.
H312: Harmful in contact with skin.

PRECAUTIONARY STATEMENT(S)

Prevention:

[201]: Obtain special instructions before use.
P202: Do not handle until all safety precautions have been read and understood.
P210: Keep away from heat/sparks/open flames/hot surfaces. – No smoking.
P233: Keep container tightly closed.
P240: Ground/bond container and receiving equipment.
P243: Take precautionary measures against static discharge.
P260: Do not breathe dust/fume/gas/mist/vapours/spray.
P264: Wash hands, forearms, and other exposed areas thoroughly after handling.

SAFETY DATA SHEET

Date Issued : 3/31/2015
MSDS No : PP EPP-VOC B

PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

P271: Use only outdoors or in a well-ventilated area.
P272: Contaminated work clothing should not be allowed out of the workplace.
P273: Avoid release to the environment.
P280: Wear protective gloves/protective clothing/eye protection/face protection.
P284: Wear respiratory protection.

Response:

P301+P310: IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
P302+P352: IF ON SKIN: Wash with plenty of soap and water.
P303+P361+P353: IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
P304+P340: IF INHALED: Remove to fresh air and keep at rest in a position comfortable for breathing.
P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P312: Call a POISON CENTER or doctor/physician if you feel unwell.
P314: Get medical advice/attention if you feel unwell.
P331: Do NOT induce vomiting.
P332+P313: If skin irritation occurs: Get medical advice/attention.
P333+P313: If skin irritation or rash occurs: Get medical advice/attention.
P337+P313: If eye irritation persists: Get medical advice/attention.
P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
P362: Take off contaminated clothing and wash before reuse.
P370+P378: In case of fire: Use appropriate media to extinguish.
P391: Collect spillage.

Storage:

P403+P233: Store in a well-ventilated place. Keep container tightly closed.
P403+P235: Store in a well-ventilated place. Keep cool.
P405: Store locked up.

Disposal:

P501: Dispose of contents/container according to local, regional, national, and international regulations.

EMERGENCY OVERVIEW

IMMEDIATE CONCERNS: WARNING! Combustible liquid and vapor. Vapors may cause flash fire. Harmful or fatal if swallowed.

POTENTIAL HEALTH EFFECTS

EYES: Can cause severe eye irritation and corneal damage.

SKIN: Can cause skin irritation; itching, redness, rashes, hives, burning, and swelling.

INGESTION: Can cause gastrointestinal irritation, nausea and vomiting. Aspiration of material into the lungs may cause chemical pneumonitis, which can be fatal. Harmful or fatal if swallowed.

INHALATION: May cause nose or throat irritation. High concentrations may lead to central nervous system effects (drowsiness, dizziness, nausea, headaches, paralysis and loss of consciousness).

ROUTES OF ENTRY: Eye and Skin Contact, Inhalation and Ingestion

IRRITANCY: Eyes, nose, throat, respiratory tract, and skin irritation.

3. COMPOSITION / INFORMATION ON INGREDIENTS

SAFETY DATA SHEET

Date Issued : 3/31/2015
MSDS No : PP EPP-VOC B

PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

Chemical Name	Wt. %	CAS
p-Chlorobenzotrifluoride	< 15	98-56-6
2,4,6-tris(dimethylaminomethyl)phenol	< 5	90-72-2
2,2'-iminodiethylamine	< 2.5	111-40-0

4. FIRST AID MEASURES

EYES: Immediately flush eyes with plenty of tempered water (at least 15-20 minutes) lifting upper and lower eye lids occasionally. Get immediate medical attention.

SKIN: Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Get medical attention if symptoms occur. Wash or dispose of clothing before reuse.

INGESTION: Do not induce vomiting, keep person warm, quiet and get medical attention immediately. If vomiting occurs naturally, have victim lean forward to reduce the risk of aspiration. Aspiration of this material into the lungs due to vomiting can cause chemical pneumonitis which can be fatal.

INHALATION: Remove to fresh air. If not breathing, give artificial respiration or give oxygen by trained personnel. Seek immediate medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

EYES: Liquid and vapor can severely irritate the eyes depending on type of exposure (splash, vapor) and exposure time.

SKIN: Mild to moderate skin irritant.

INGESTION: May result in central nervous system (CNS) depression with symptoms such as headaches, nausea, vomiting, diarrhea, dizziness, incoordination and unconsciousness. Aspiration of material into lungs may cause chemical pneumonitis which can be fatal.

INHALATION: High vapor concentrations may cause CNS depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion, and unconsciousness.

ACUTE TOXICITY: High vapor concentrations may cause central nervous system (CNS) depression with symptoms including light headedness, giddiness, nausea, drowsiness, headache, nose, throat and respiratory tract irritation, reduced appetite, confusion and unconsciousness.

CHRONIC EFFECTS: Damage to the nervous system of the extremities, peripheral neuropathy, with symptoms including numbness, tingling and weakness in the toes and fingers, sensory impairment to touch, pain, vibration and temperature, muscular weakness, blurred vision, coldness of extremities, loss of body weight and reflexes, and even paralysis. Frequent or prolonged contact may irritate the skin and cause a skin rash (dermatitis).

5. FIRE FIGHTING MEASURES

FLAMMABLE CLASS: Class II

GENERAL HAZARD: Combustible Liquid.

EXTINGUISHING MEDIA: Foam, dry chemical, carbon dioxide, water spray or fog.

EXPLOSION HAZARDS: Containers exposed to intense heat from fires should be cooled with water to prevent vapor pressure buildup which could result in container rupture. Container areas exposed to direct flame contact should be cooled with large quantities of water as needed to prevent weakening of container structure.

FIRE FIGHTING PROCEDURES: As in any fire, wear self-contained breathing apparatus with pressure-demand, full face piece SCBA (MSHA/NIOSH approved or equivalent) and full protective gear.

SENSITIVITY TO IMPACT: None known.

SAFETY DATA SHEET

Date Issued : 3/31/2015
MSDS No : PP EPP-VOC B

PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

HAZARDOUS DECOMPOSITION PRODUCTS: Decomposition products may include oxides of carbon and nitrogen.

6. ACCIDENTAL RELEASE MEASURES

SMALL SPILL: Dike area to contain spill. Take precautions as necessary to prevent contamination of ground and surface waters. Recover spilled material on absorbent, such as sawdust or vermiculite, and sweep into closed containers for disposal. Do not flush to sewer. If area of spill is porous, remove as much contaminated earth and gravel, etc. as necessary and place in closed containers for disposal. Only those persons who are adequately trained, authorized, and wearing the appropriate personal protective equipment (PPE) should participate in spill response and clean-up.

LARGE SPILL: Keep spectators away. Only those persons who are adequately trained, authorized and wearing the required personal protective equipment (PPE) should participate in spill response and clean-up. Know and prepare for spill response before using or handling this product. Dike and contain spill with inert material (e.g. sand, earth). Transfer liquids to covered and labeled containers for disposal. Use appropriate PPE. Place absorbent diking materials in covered containers for disposal. Prevent contamination of sewers, streams, and groundwater with spilled material or used absorbent.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: For professional or industrial use only. Follow label instructions. Keep out of the reach of children. Not for consumption. No smoking. Do not breathe vapors. Avoid contact with body. Turn off all pilot lights, flames, stoves, heaters, electric motors, welding equipment and other sources of ignition. Empty containers must not be washed and re-used for any purpose. Contact lens wearers must wear protective eye wear around chemical vapors and liquid. Wash hands thoroughly after handling. To prevent build-up of vapors, use adequate natural and/or mechanical ventilation (e.g. open all windows and doors to achieve cross ventilation). Vapors may be heavier than air and will collect in low areas. Containers may be hazardous when empty.

HANDLING: Use adequate ventilation and appropriate respiratory protection to avoid breathing vapors when cover is removed. Ground and bond all equipment when handling flammable solvent-borne material.

STORAGE: Keep container closed when not in use. Store in a dry, well ventilated area, out of the sun and away from ignition sources. Do not remove or deface label. Prevent water or moist air from entering container.

STORAGE TEMPERATURE: 15.5°C (60°F) Minimum to 35°C (95°F) Maximum

SHELF LIFE: 1 year from manufacture date

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

SAFETY DATA SHEET

Date Issued : 3/31/2015
MSDS No : PP EPP-VOC B

PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)					
		EXPOSURE LIMITS			
		OSHA PEL		ACGIH TLV	
Chemical Name		ppm	mg/m ³	ppm	mg/m ³
p-Chlorobenzotrifluoride	TWA	NL [1]	NL [1]	NL [1]	NL [1]
	STEL	NL [1]	NL [1]	NL [1]	NL [1]
2,4,6-tris(dimethylaminomethyl)phenol	TWA	NL [1]	NL [1]	NL [1]	NL [1]
	STEL	NL [1]	NL [1]	NL [1]	NL [1]
2,2'-iminodiethylamine	TWA	NL [1]	NL [1]	1 ppm [1]	NL [1]
	STEL	NL [1]	NL [1]	NL [1]	NL [1]
Footnotes:					
1. NL = Not Listed					

ENGINEERING CONTROLS: Provide sufficient explosion proof mechanical (general and/or local exhaust) ventilation to maintain exposure below the occupational exposure limit and exposure concentration.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Wear safety glasses with side shields (or goggles) or a full face respirator.

SKIN: Wear chemical protective clothing & boots to prevent repeated or prolonged skin contact. Wear impervious gloves, if needed, to prevent repeated or prolonged skin contact.

RESPIRATORY: NIOSH/MSHA approved air purifying respirator with an organic vapor cartridge or canister may be permissible under certain circumstances where airborne concentrations are expected to exceed exposure limits. Protection provided by air purifying respirators is limited. Use a positive pressure air supplied respirator if there is any potential for an uncontrolled release, exposure levels are not known, or any other circumstances where air purifying respirators may not provide adequate protection. A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

PROTECTIVE CLOTHING: Wear chemical resistant gloves, such as nitrile rubber.

WORK HYGIENIC PRACTICES: Use good hygiene practices when handling this material. Wash hands thoroughly after use.

9. PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE: Liquid

ODOR: Mild to moderate amine odor

ODOR THRESHOLD: Not Determined

COLOR: Clear to Straw Yellow

pH: Not Determined

PERCENT VOLATILE: 11.0

Notes: by weight

FLASHPOINT AND METHOD: 43.3°C (110°F)

SAFETY DATA SHEET

Date Issued : 3/31/2015
MSDS No : PP EPP-VOC B

PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

FLAMMABLE LIMITS: Not Available to Not Available

VAPOR PRESSURE: Not Determined

VAPOR DENSITY: Not Determined

BOILING POINT: Not Determined

FREEZING POINT: Not Determined

MELTING POINT: Not Determined

POUR POINT: Not Determined

SOLUBILITY IN WATER: Slight

EVAPORATION RATE: > 1.0 (n-Butyl Acetate=1)

DENSITY: 8.46 lbs/gal

PARTICLE SIZE: Not Determined

SPECIFIC GRAVITY: 1.015

VISCOSITY: Not Determined

MOLECULAR WEIGHT: Not Determined

(VOC): 65.000 gr/L EPA Method 24 VOC

COEFF. OIL/WATER: Not Determined

OXIDIZING PROPERTIES: Not Determined

10. STABILITY AND REACTIVITY

STABLE: Yes

HAZARDOUS POLYMERIZATION: No

STABILITY: Stable.

POLYMERIZATION: Product will not undergo polymerization.

CONDITIONS TO AVOID: Avoid exposure to high temperature. Avoid heat, sparks and flame.

POSSIBILITY OF HAZARDOUS REACTIONS: None Expected.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, oxides of nitrogen, nitric acid

INCOMPATIBLE MATERIALS: Strong oxidizing agents, strong acids (e.g. sulfuric acid, acetic acid, citric acid), reactive organometallic compounds, peroxides, sodium hypochlorite.

11. TOXICOLOGICAL INFORMATION

ACUTE

Chemical Name	ORAL LD ₅₀ (rat)	DERMAL LD ₅₀ (rabbit)	INHALATION LC ₅₀ (rat)
p-Chlorobenzotrifluoride	> 6800 mg/kg	> 2700 mg/kg	4479 ppm (4-hr dose)
2,4,6-tris(dimethylaminomethyl)phenol	2169 mg/kg (rats)	No data	No data
2,2'-iminodiethylamine	1080 mg/kg (rats)	1090 mg/kg (rabbits)	0.3 mg/L (4-hr dose)

IRRITATION: Eyes, nose, throat, respiratory tract irritation.

SAFETY DATA SHEET

Date Issued : 3/31/2015
MSDS No : PP EPP-VOC B

PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

12. ECOLOGICAL INFORMATION

ENVIRONMENTAL DATA: This product contains components that will normally float on water. These components may be harmful to aquatic organisms and may cause long term adverse effects in the aquatic environment.

ECOTOXICOLOGICAL INFORMATION: Contains components that are potentially toxic to freshwater and saltwater ecosystems.

BIOACCUMULATION/ACCUMULATION: Contains components with the potential to bio-accumulate.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of in accordance with all local, state and federal regulations.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Non-Regulated Material per 49 CFR 173.150(f)

AIR (ICAO/IATA)

SHIPPING NAME: Not Regulated

VESSEL (IMO/IMDG)

SHIPPING NAME: Not Regulated

15. REGULATORY INFORMATION

UNITED STATES

DOT LABEL SYMBOL AND HAZARD CLASSIFICATION

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

FIRE: Yes **PRESSURE GENERATING:** No **REACTIVITY:** No **ACUTE:** Yes **CHRONIC:** Yes

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
p-Chlorobenzotrifluoride	98-56-6
2,4,6-tris(dimethylaminomethyl)phenol	90-72-2
2,2'-iminodiethylamine	111-40-0

STATES WITH SPECIAL REQUIREMENTS

Chemical Name	Requirements
p-Chlorobenzotrifluoride	New Jersey Right to Know List Pennsylvania Right to Know List
2,4,6-tris(dimethylaminomethyl)phenol	Massachusetts Right to Know List Pennsylvania Right to Know List New Jersey Right to Know List
2,2'-iminodiethylamine	Massachusetts Right to Know List Pennsylvania Right to Know List New Jersey Right to Know List

CANADA

SAFETY DATA SHEET

Date Issued : 3/31/2015
MSDS No : PP EPP-VOC B

PACIFIC POLYMERS Elasto-Poxy Primer (VOC) Component B

WHMIS HAZARD SYMBOL AND CLASSIFICATION



Toxic



Combustible
Liquid


16. OTHER INFORMATION

INFORMATION CONTACT: (714) 898-0025

HMIS RATING

HEALTH	*	2
FLAMMABILITY		2
PHYSICAL HAZARD		0
PERSONAL PROTECTION		B

NFPA CODES



GENERAL STATEMENTS: Keep out of reach of children
For professional or industrial use only

MANUFACTURER DISCLAIMER: This document may be used to comply with OSHA's Hazardous Communication Standard, 29 CFR 1910.1200.

To the best of our knowledge, the information contained in this SDS is accurate. It is intended to assist the user in his/her evaluation of the product's hazards and safety precautions to be taken in its use. The data in this SDS relate only to the specific material designated herein. We do not assume liability for the use of, or reliance on this information, nor do we guarantee its accuracy or completeness.

This information is furnished without warranty, expressed or implied, except that it is accurate to the best knowledge of ITW Polymers Sealants North America. The data on this sheet relates only to the specific material designated herein. ITW Polymers Sealants North America assumes no legal responsibility for use or reliance upon these data.