Material Safety Data Sheet Date last revised: April, 2001

Date last revised: April, 2001				
I. GENERAL INFORMATION				
Chemical Name & Synonyms AROMATIC ISOCYANATE	Trade Name & Synonyms DYNATROL II ACTIVATOR (Part A)			
Chemical Family	Formula			
URETHANE	MIXTURE			
Proper DOT Shipping	DOT Hazard Classification			
CAULKING COMPOUND Manufacturer	N/A Manufacturer's Phone Number			
PECORA CORPORATION	215-723-6051			
Manufacturer's Address 165 Wambold Road, Harleysville, PA 19438	Chemtrec Phone Number 800-424-9300			
II. INGREDIENTS				
Principal Hazardous Components	Percent	Threshold Limit Value (Units)		
TOULENE DIISOCYANATE (CAS #26471-62-5)	< 5 > 95	0.02 PPM PEL		
URETHANE PREPOLYMER	> 95	NOT ESTABLISHED		
THIS PRODUCT CONTAINS TOLUENE				
DIISOCYANATE WHICH IS SUBJECT TO THE				
REPORTING REQUIREMENTS OF SECTION 313				
OF SARA. THIS PRODUCT CONTAINS A				
CHEMICAL KNOWN TO THE STATE OF				
CALIFORNIA TO CAUSE CANCER.				
HEALTH 3 FLAMMABILITY 1		REACTIVITY 2		
III. PHY	SICAL DATA			
Boiling Point (°F) Specific Gravity $(H_20 = 1)$				
484° F. (TDI)	1.05			
Vapor Pressure (mm Hg.)	Percent Volatile by Volume (%)			
0.025 @ 77° F. (TDI) Vapor Density (Air = 1)	NEGLIGIBLE Evenoration Pata (ETHER= 1)			
vapor Density (Air = 1) 6.0 (TDI)	Evaporation Rate (ETHER= 1) SLOWER			
Solubility in Water	PH PH			
N/A				
INSOLUBLE				
Appearance & Odor CLEAR, LIGHT YELLOW LIQUID – TDI ODOR				
IV. FIRE & EXPLOSION HAZARD DATA				
Flash Point (Test Method)	Auto Ignition Temp			
> 200° F.	UNKNOWN			
Flammable Limits	LEL	UEL		
UNKNOWN	UNKNOWN	UNKNOWN		
OTAMAO WIY				
Extinguishing Media Small Fires: DRY CHEMICAL, WATER FOG, FOAM & CHEMCIALS	I			
Special Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS SHOULD BE WORN WHEN FIGHTING				
FIRES INVOLVING CHEMCIALS.				
Unusual Fire & Explosion Hazards: AT TEMPERATURES GREATER THAN 350° F. (177° C.), TDI FORMS CARBODIIMIDES				
WITH THE RELEASE OF CO ₂ WHICH CAN CAUSE PRESSURE BUILD UP IN CLOSED CONTAINERS. USE COLD WATER TO COOL FIRE-EXPOSED CONTAINERS				
TO COOL I INL-LAI ODED CONTAINERD				

DYNATROL –II ACTIVATOR (PART A) PAGE 2 OF 2				
V. Health Hazard Data				
OSHA Permissible SEE SECTION II	Exposure Limit	ACGIH Threshold Limit Value SEE SECTION II		
Carcinogen – TDI		Carcinogen – TDI		
Symptoms of Exposure: NO ILL EFFECTS IN THE NORMAL USE OF THIS COMPOUND. INHALATION OF VAPORS MAY CAUSE IRRITATION TO LUNGS AND PULMONARY. EDEMA MAY OCCUR AFTER A SERIOUS VAPOR EXPOSURE. PULMONARY SENSITIZATION CAN OCCUR IN SOME INDIVIDUALS.				
		: PRECLUDE FROM EXPOSURE THOSE INDIVIDUALS HAVING A HISTORY OF ONDITIONS, EYE DAMAGE AND TDI SENSITIZATION.		
Primary Route (s) of Entry: DERMAL AND INHALATION				
Emergency First Aid: SKIN: WASH WITH SOAP AND WATER. INHALATION: MOVE TO FRESH AIR. AID BREATHING IF NECESSARY. OBTAIN MEDICAL ATTENTION IMMEDIATELY. EYES: FLUSH WITH WATER FOR 15 MINUTES. INGESTION: GIVE LARGE AMOUNTS OF WATER TO DILUTE MATERIAL AND CONSULT A PHYSICIAN IMMEDIATELY.				
VI. REACTIVITY DATA				
Stability	Unstable	Conditions to Avoid		
	Stable	Conditions to Avoid HIGH TEMPERATURES		
		Materials to Avoid WATER OR MOISTURE AND ANY OTHER PRODUCTS THAT REACT WITH ISOCYANATES.		
Hazardous	May Occur	Conditions to Avoid		
Polymerization	Will Not Occur	Conditions to Avoid HIGH TEMPERATURES AND CONTACT WITH MOISTURE.		
Hazardous Decomposition Products: TDI VAPORS, OXIDES OF NITROGEN, CO AND HCN				
VII. ENVIRONMENTAL PROTECTION PROCEDURES Spill Response: SCRAPE UP AND PLACE IN CONTAINERS. ALLOW TO HARDEN IN OPEN CONTAINERS. CO ₂ WILL BE EVOLVED. FINISH CLEANING AREA WITH A SOLVENT SUCH AS CELLOSOLVE ACETATE. FOLLOW SOLVENT MANUFACTURER'S PRECAUTIONS.				
Waste Disposal Method: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.				
	VIII.	SPECIAL PROTECTION INFORMATION		
Eye Protection Skin Protection				
GLASSES OR GOGGLES Respiratory Protection (Specific Type) NIOSH ORGANIC VAPOR Ventilation Recommended				
RESPIRATOR FOR CONFINED AREAS LOCAL OR MECHANICAL Other Protection:				
BARRIER SKIN CREAM				
IX. SPECIAL PRECAUTIONS Hygienic Practices In Handling & Storage: WASH HANDS AFTER USE AND BEFORE EATING OR SMOKING. STORE IN				
UNOPENED CONATINERS AT OR BELOW 80° F. (27° C.) TO PROLONG SHELF LIFE.				
Precautions For Repair & Maintenance of Contaminated Equipment: SEE SECTION VI & VIII				
Other Precautions: THIS PRODUCT CONTAINS DIISOCYANATES. AVOID PROLONGED BREATHING OF VAPORS AND CONTACT WITH EYES AND SKIN. FOR COMMERCIAL USE ONLY.				
	KF	EP OUT OF REACH OF CHILDREN!!!!!		