



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikadur® 35 Hi-Mod LV PART A** REVISION DATE: February 1st, 2015

USAGE: HIGH MODULUS, HIGH RESISTANCE, LOW VISCOSITY EPOXY GROUTING / SEALING / BINDING ADHESIVE

MANUFACTURER/SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: Not regulated WHMIS Classification: D2B
UN NUMBER: Not established Class: Not applicable
Packaging Group: Not applicable

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
EPOXY RESIN	60-100	Not Available	25085-99-8	> 5000 (oral, rat)	Not Available
NONYL PHENOL	1-5	Not Available	84852-15-3	580 (oral, rat)	Not Available
PETROLEUM DISTILLATE	1-5	Not Available	68477-31-6	2622 (oral, rat)	Not Available

SECTION III: PHYSICAL CHARACTERISTICS

Physical State:	Liquid	Boiling Point:	Not Established
Appearance and Odor:	Amber Liquid, ether odor	Freezing Point:	Not Established
		Density:	1.1 g/ml
Odor Threshold:	Not Established	Water Solubility:	No
Evaporation Rate:	Not Applicable	pH:	Not Established
Vapor Density:	Not Established	% volatility:	Not Applicable
Vapor Pressure:	Not Established	Water/Oil Distribution:	Not Established



PRODUCT: **Sikadur® 35 Hi-Mod LV** PART A

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: If Yes, under what conditions:	No	TDG Flammability Class:	Not Regulated
Extinguishing methods:	Foam, dry chemical products, CO ₂ , water hose.	Flammable upper limits (% vol.):	Not Applicable
Special Methods:	Fire fighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.	Flammable lower limits (% vol.):	Not Applicable
		Flash Point (method used):	110°C
		Auto-ignition temperature:	Not Established
		Dangerous Combustion Products:	Carbon oxides, phenol
		Protect from mechanical impact:	No
		Protect from static discharge:	No

SECTION V: REACTIVITY DATA

Chemical stability: If not, under what conditions:	Yes But excessive heat will degrade the resin.	Dangerous decomposition products:	Carbon oxides, phenol
Incompatibility with other material: If Yes, which ones:	Yes Base, strong acid, oxidizer.	Polymerization Risks:	May polymerize at very high temperatures.



PRODUCT: Sikadur® 35 Hi-Mod LV PART A

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations.

Carcinogenicity: Not Established

Skin: May be irritating to the skin, may cause sensitization.

Toxic effects on reproduction: Not Established

Inhalation: Mist of the product may irritate lungs, may cause an allergic reaction, if the product is sprayed,

Teratogenicity: Not Established

Ingestion: May cause irritation of the gastrointestinal system.

Mutagenicity: Not Established

Product with synergistic effects: Not Established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: Sikadur® 35 Hi-Mod LV PART A

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: Not necessary under normal use.

Eyes: Safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case of leaks: Absorb with sand or other absorbent material. Residue may be removed with steam or hot water and soap. All precautions should be taken when cleaning the spill with solvent.

Handling and Equipment Methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikadur® 35 Hi-Mod LV PART A

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of soap and water.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water for at least 15 minutes to ensure a proper wash.
Consult a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.



SECTION I: PRODUCT INFORMATION

PRODUCT: **Sikadur® 35 Hi-Mod LV PART B** REVISION DATE: July 27th, 2015

USAGE: HIGH-MODULUS, LOW VISCOSITY, HIGH-STRENGTH, EPOXY GROUTING / SEALING / BINDING ADHESIVE

MANUFACTURER/SUPPLIER: SIKA CANADA INC.
601, avenue Delmar
Pointe Claire, QC
H9R 4A9

EMERGENCY TELEPHONE NUMBER: CANUTEC (collect) (613) 996-6666

TDG CLASSIFICATION: CORROSIVE LIQUID, BASIC, ORGANIC, N.O.S. (Isophorone diamine, nonylphenol)

WHMIS Classification: D2A, E

UN NUMBER: 3267 Class: 8

Packaging Group: II

SECTION II: HAZARDOUS INGREDIENTS

Hazardous ingredients	%	T.L.V.	# CAS	LD ₅₀ (mg/kg) (species, route)	LC ₅₀ (species, route)
BENZYL ALCOHOL	10-30	Not Available	100-51-6	1230 (oral, rat)	4000mg/m ³ rat
ISOPHORONE DIAMINE	10-30	Not Available	2855-13-2	Not Available	Not Available
NONYL PHENOL	10-30	Not Available	84852153	580 (oral, rat)	Not Available
TRI DIMETHYL AMINE METHYL PHENOL 2, 4, 6	10-30	Not Available	90-72-2	Not Available	Not Available
NAPHTHALENE	1-2	Not Available	91-20-3	Not Available	Not Available

SECTION III: PHYSICAL CHARACTERISTICS

Physical State:	Liquid	Boiling Point:	Not Established
Appearance and Odor:	Amber liquid with amine odor	Freezing Point:	Not Established
		Density:	0.98 g/ml
Odor Threshold:	Not Established	Water Solubility:	Partial
Evaporation Rate:	Not Applicable	pH:	Not Established
Vapor Density:	Not Applicable	% volatility:	Not Established
Vapor Pressure:	Not Applicable	Water/Oil Distribution:	Not Established



PRODUCT: Sikadur® 35 Hi-Mod LV PART B

SECTION IV: FIRE AND EXPLOSION HAZARDS

Flammability: No
 If Yes, under what conditions: But avoid fire and spark

Extinguishing methods: Foam, dry chemical products, CO₂, water hose.

Special Methods: Fire fighters must wear usual protective clothing and respiratory equipment. A water hose may be used to cool the containers and dissipate the vapors.

TDG Flammability Class: None
 Flammable upper limits (% vol.): Not Established
 Flammable lower limits (% vol.): Not Established
 Flash Point (method used): > 100°C
 Auto-ignition temperature: Not Established
 Dangerous Combustion Products: Carbon oxides, nitrogen oxide, ketone, aldehyde.

Protect from mechanical impact: No
 Protect from static discharge: No

SECTION V: REACTIVITY DATA

Chemical stability: Yes
 If not, under what conditions:

Incompatibility with other material: Yes
 If Yes, which ones: Acid, strong oxidizers.

Dangerous decomposition products: Carbon oxides, nitrogen oxide

Polymerization Risks: No



PRODUCT: Sikadur® 35 Hi-Mod LV PART B

SECTION VI: TOXIC PROPERTIES

ROUTE OF ENTRY / CONTACT

Eyes: May cause eye irritations. May cause severe burns. May cause blindness.

Skin: May be irritating to the skin, may cause severe burns, can be absorbed by skin. Contact may cause necrosis, dermatitis, allergic reactions, and sensitization.

Inhalation: Vapor or mist of this product may cause irritation if product would be sprayed.

Ingestion: May cause severe burns to the mouth, throat, stomach, nausea, diarrhea, vomiting, damage to the lungs, fainting, death.

An over-exposure may cause breathing difficulty, headaches, nausea, damages to the lungs, sensitization. May aggravate skin, eyes, respiratory or allergic problems.

Carcinogenicity: Not Established

Toxic effects on reproduction: Not Established

Teratogenicity: Yes, when laboratory animals were force fed with high dose.

Mutagenicity: Yes

Product with synergistic effects: Not Established

An acute or chronic exposure will increase the toxic effects mentioned in this section and may aggravate respiratory problems.



PRODUCT: Sikadur® 35 Hi-Mod LV PART B

SECTION VII: PREVENTIVE MEASURES

PERSONAL PROTECTIVE EQUIPMENT

Gloves: Chemical resistant gloves.

Respiratory equipment: Use a properly fitted NIOSH approved air-purifying or air-fed respirator complying with an approved standard if a risk assessment indicates this is necessary.

Eyes: Full face mask or safety glasses

Shoes: Leather

Clothing: Rubber Apron

Other: Eye wash station, shower

OTHERS

Ventilation: Sufficient ventilation required

Procedure in case Of leaks Absorb with sand or other absorbent material.

Handling and Equipment Methods: Avoid skin, eye and clothing contact

Warehouse Requirements: Keep all containers closed in a cool, dry area. Keep away from heat and open flame.

Special Shipping Instructions: See TDG class

Waste Disposal: Dispose of sand and rinse water according to municipal, provincial or federal laws for disposal of chemicals.



PRODUCT: Sikadur® 35 Hi-Mod LV PART B

SECTION VIII: FIRST AID

Skin: Remove contaminated clothing and shoes.
Wash immediately with plenty of soap and water.
Throw away shoes that were soiled on the inside.
Wash clothing before re-wearing.
Consult a physician if required.

Eyes: Rinse eyes immediately with plenty of water for several minutes, while holding eyelids wide open, to ensure a proper wash.
The eye rinse within the first minute is essential to ensure maximum protection.
Consult a physician immediately.

Inhalation: In the case of overexposure, evacuate to fresh air.
Consult a physician if required.

Ingestion: Drink plenty of water. Do not induce vomiting.
Do not give anything by mouth to an unconscious person.
See a physician immediately.

SECTION IX: PREPARATION INFORMATION

Prepared By: R & D of Sika Canada Inc.
Telephone #: (514) 697-2610
Fax #: (514) 694-2792

Notice To Reader

The information contained in this Material Safety Data Sheet applies only to the actual Sika Canada product identified and described herein. This information is not intended to address, nor does it address the use or application of the identified Sika product in combination with any other material, product or process. All of the information set forth herein is based on technical data regarding the identified product that Sika believes to be reliable as of the date hereof. Prior to each use of any Sika product, the user must always read and follow the warnings and instructions on the product's current Product Data Sheet, product label and Material Safety Data Sheet for each Sika product, which are available at web site and/or telephone number listed in Section IX of this MSDS.

SIKA MAKES NO WARRANTIES EXPRESS OR IMPLIED AND ASSUMES NO LIABILITY ARISING FROM THIS INFORMATION OR ITS USE. SIKA SHALL NOT BE LIABLE UNDER ANY LEGAL THEORY FOR SPECIAL OR CONSEQUENTIAL DAMAGES AND SHALL NOT BE RESPONSIBLE FOR THE USE OF THIS PRODUCT IN A MANNER TO INFRINGE ON ANY PATENT OR ANY OTHER INTELLECTUAL PROPERTY RIGHTS HELD BY OTHERS.

All sales of Sika products are subject to its current terms and conditions of sale available at www.sika.ca or 514-697-2610.