

Version 2.0 Print Date 07/09/2012

**REVISION DATE: 07/08/2012** 

### **SECTION 1 - PRODUCT IDENTIFICATION**

Trade name : EXOAIR 220-R 5 GAL PAIL

Product code : 584333 805

COMPANY : Tremco Incorporated

3735 Green Road Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST

ne: : (216) 765-6727 8:30 - 5:00 EST After Hours: Chemtrec 1-800-424-9300

### **SECTION 2 - HAZARDS IDENTIFICATION**

### **Emergency Overview**

Brown. Liquid. May cause slight irritation to the respiratory system. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

## **Acute Potential Health Effects/ Routes of Entry**

Inhalation : May cause slight irritation to the respiratory system.

Eyes : Direct contact may cause mild irritation.

Ingestion : May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause mild irritation. May cause sensitization resulting in irritation, itching and

redness. May cause a rash.

#### **Aggravated Medical Conditions**

Pre-existing eye, skin and respiratory disorders may be aggravated by exposure.

## **Chronic Health Effects**

Prolonged or repeated skin contact with asphalt may result in skin sensitivity, such as irritation, rashes, and dermatitis. Prolonged or repeated exposure to polycyclic aromatic hydrocarbons and other volatiles which are contained in trace amounts in asphalt have been shown to cause cancer or respiratory damage in animals. Fillers are encapsulated and not expected to be released from product under normal conditions of use.

Target Organs: Skin, Eye, Lung

### **SECTION 3 - PRODUCT COMPOSITION**

Chemical Name	CAS-No.	Weight %
Water	7732-18-5	40.0 - 70.0
Acrylic Polymer	NJ TSRN# 51721300-5816P	30.0 - 60.0
Asphalt	8052-42-4	15.0 - 40.0

### **SECTION 4 - FIRST AID MEASURES**

Get immediate medical attention for any significant overexposure.

Inhalation : Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get

medical attention.

An **RPIII** Company 1/5 584333 805

# Material Safety Data Sheet



## EXOAIR 220-R 5 GAL PAIL

Version 2.0 Print Date 07/09/2012

**REVISION DATE: 07/08/2012** 

Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical

attention immediately.

Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other

disorders develop, get medical attention immediately.

Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control

Center or Physician immediately.

### SECTION 5 - FIRE FIGHTING MEASURES

Flash point : Not available.

Method : Not available.

Lower explosion limit : Not available.

Upper explosion limit : Not available.

Autoignition temperature : Not available.

Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.

Hazardous combustion : Carbon monoxide and carbon dioxide can form.Oxides of sulfur can

products

Protective equipment for :

firefighters

Not applicable. Product is not expected to burn.

Fire and explosion conditions : Not applicable, not expected to burn.

### **SECTION 6 - ACCIDENTAL RELEASE MEASURES**

Use appropriate protective equipment. Avoid contact with material. Stop flow. Contain spill. Keep out of water courses. Absorb spill in sand, earth or other suitable material. Transfer to appropriate container for disposal.

### SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. Store in sealed containers in a dry, ventilated warehouse location above freezing.

### SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

### Personal protection equipment

Respiratory protection : Not required under normal conditions of use.

Hand protection : Use suitable impervious rubber or vinyl gloves and protective apparel to

reduce exposure.

Eye protection : Wear chemical safety goggles and/or face shield to prevent eye contact. Do

not wear contact lenses. Do not touch eyes with contaminated body parts or

materials. Have eye washing facilities readily available.

Protective measures : Use professional judgment in the selection, care, and use. Other equipment

not normally required.

Engineering measures : General ventilation is sufficient. Use local exhaust when the general

ventilation is inadequate.

An **RPI** Company 2/5 584333 805



Version 2.0 Print Date 07/09/2012

**REVISION DATE: 07/08/2012** 

### **Exposure Limits**

Chemical Name	CAS Number	Regulation	<u>Limit</u>	<u>Form</u>
Asphalt	8052-42-4	ACGIH TWA: benzene solubles	0.5 mg/m3	Inhalable fraction.as

## **SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Form : Liquid Color : Brown Odor : Asphalt : 8.6 - 9.5 Hq Vapour pressure : Not available. Vapor density : Heavier than air Melting point/range : Not available. Freezing point : Not available. Boiling point/range : Not available. Water solubility : Dispersible Specific Gravity : 1.042 % Volatile Weight : 40 %

## **SECTION 10 - REACTIVITY / STABILITY**

Substances to avoid : Oxidizing agents.

Stability : Material is stable under normal storage, handling, and use.

Hazardous polymerization : Will not occur under normal conditions.

## **SECTION 11 - TOXICOLOGICAL INFORMATION**

No Data Available

## **SECTION 12 - ECOLOGICAL INFORMATION**

No Data Available

## **SECTION 13 - DISPOSAL CONSIDERATIONS**

Disposal Method : Waste not regulated under RCRA. Incinerate at EPA approved facility or dispose of

waste in compliance with state and local regulations.



Version 2.0 Print Date 07/09/2012

**REVISION DATE: 07/08/2012** 

## SECTION 14 - TRANSPORTATION / SHIPPING DATA

### CFR / DOT:

Not Regulated

TDG:

Not Regulated

IMDG:

Not Regulated

### **SECTION 15 - REGULATORY INFORMATION**

#### **North American Inventories:**

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

**U.S. Federal Regulations:** 

SARA 313 Components : None present or none present in regulated quantities.

SARA 311/312 Hazards : Acute Health Hazard

OSHA Hazardous Components:

Asphalt 8052-42-4

OSHA Status: Considered

hazardous based on the

following criteria:

: Irritant

OSHA Flammability : Not Regulated

Regulatory VOC (less water and

exempt solvent)

: 2 g/l

VOC Method 310 : 0 %

**U.S. State Regulations:** 

MASS RTK Components : Asphalt 8052-42-4

Penn RTK Components : Water 7732-18-5

Acrylic Polymer NJ TSRN# 51721300-5816P

Asphalt 8052-42-4

NJ RTK Components : Water 7732-18-5

Acrylic Polymer NJ TSRN# 51721300-5816P

An **RPM** Company 4/5 584333 805



Version 2.0 Print Date 07/09/2012

**REVISION DATE: 07/08/2012** 

Asphalt 8052-42-4

Components under California Proposition 65:

WARNING! Contains chemicals known to the State of California to cause cancer, birth defects and/or other reproductive harm

### **SECTION 16 - OTHER INFORMATION**

## **HMIS Rating:**

Health	1	0 = Minimum
Flammability	0	1 = Slight
Reactivity	0	2 = Moderate
PPE		3 = Serious
		4 = Severe

### **Further information:**

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

### Prepared by: Rich Mikol

#### Legend

ACGIH - American Conference of Governmental Hygienists

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

DOT - Department of Transportation

DSL - Domestic Substance List

EPA - Environmental Protection Agency

HMIS - Hazardous Materials Information System

IARC - International Agency for Research on Cancer

MSHA - Mine Safety Health Administration

NDSL - Non-Domestic Substance List

NIOSH - National Institute for Occupational Safety and Health

NTP - National Toxicology Program

OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit

RCRA - Resource Conservation and Recovery Act

RTK - Right To Know

SARA - Superfund Amendments and Reauthorization Act

STEL - Short Term Exposure Limit

TLV - Threshold Limit Value

TSCA - Toxic Substances Control Act

TWA - Time Weighted Average

V - Volume

VOC - Volatile Organic Compound

WHMIS - Workplace Hazardous Materials Information

System