

TREMPROOF 250 GC-R 5 GAL PAIL

Version 1

Print Date 11/30/2005

REVISION DATE: 05/06/2005

SECTION 1 - PRODUCT IDENTIFICATION

Trade name : TREMPROOF 250 GC-R 5 GAL PAIL
Product code : 304510 805

COMPANY : Tremco Incorporated
3735 Green Road
Cleveland, OH 44122

Telephone : (216) 292-5000 8:30 - 5:00 EST
Emergency Phone: : (216) 765-6727 8:30 - 5:00 EST
After Hours: Chemtrec 1-800-424-9300

Product use : Coating

SECTION 2 - HAZARDS IDENTIFICATION**Emergency Overview**

Black. Liquid. May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue. Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.

Acute Potential Health Effects/ Routes of Entry

Inhalation : May cause moderate irritation to the respiratory system. May cause nausea, headaches, and dizziness. May cause drowsiness, weakness, and fatigue.

Eyes : Vapor and/or mist may cause eye irritation. Direct contact may cause temporary redness and discomfort.

Ingestion : May cause irritation to the mouth, throat and stomach. May cause gastrointestinal irritation, nausea, and vomiting.

Skin : May cause moderate irritation.

Aggravated Medical Conditions

Pre-existing eye, skin, liver, kidney, and respiratory disorders may be aggravated by exposure.

Chronic Health Effects

Reports have associated repeated and prolonged occupational overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling contents may be harmful or fatal. Aromatic tar contains polycyclic aromatic hydrocarbons, some of which have been shown to cause skin cancer following prolonged and repeated skin contact. Should be considered potentially carcinogenic by inhalation. Carbon black is classified by IARC to be a known animal carcinogen and a possible human carcinogen (Group 2B). Carbon black is encapsulated by resin and not expected to have adverse effects unless made airborne. The International Agency for Research on Cancer (IARC) has evaluated ethylbenzene and classified it as a possible human carcinogen (Group 2B) based on sufficient evidence for carcinogenicity in experimental animals, but inadequate evidence for cancer in exposed humans. Prolonged and repeated exposure to excessive airborne concentrations of talc can result in scarring of the lungs (pneumoconiosis) or the covering of the lungs (pleural thickening). Fillers are encapsulated and not expected to be released from product under normal conditions of use. Prolonged or repeated exposure to mineral spirits (petroleum naphtha or stoddard solvent) may cause defatting, drying, and irritation of the skin, dermatitis, central nervous system (CNS) effects, and adverse liver, kidney, and lung effects.

Target Organs: Skin, Eye, Lung, Liver, Kidney, Nerve, Reproductive

TREMPROOF 250 GC-R 5 GAL PAIL

Version 1

Print Date 11/30/2005

REVISION DATE: 05/06/2005

SECTION 3 - PRODUCT COMPOSITION

Chemical Name	CAS-No.	Weight %
Aromatic process oil	64742-90-1	30.0 - 60.0
Polyurethane Polymer	NJ TSRN# 51721300-5358P	15.0 - 40.0
Calcium carbonate	471-34-1	7.0 - 13.0
Stoddard solvent	8052-41-3	7.0 - 13.0
Polyvinyl chloride	9002-86-2	5.0 - 10.0
Carbon Black	1333-86-4	3.0 - 7.0
1,2-Benzenedicarboxylic acid	68515-44-6	1.0 - 5.0
1,2-Benzenedicarboxylic acid	68515-45-7	1.0 - 5.0
1,2-Benzenedicarboxylic acid	111381-89-6	1.0 - 5.0
Talc	14807-96-6	1.0 - 5.0
Anthracene	120-12-7	1.0 - 5.0
Xylene	1330-20-7	1.0 - 5.0
Ethylbenzene	100-41-4	- <1.0

SECTION 4 - FIRST AID MEASURES

Get immediate medical attention for any significant overexposure.

- Inhalation : Move to fresh air. If required, artificial respiration or administration of oxygen can be performed by trained personnel. Leave area to breathe fresh air. Avoid further overexposure. If symptoms persist, get medical attention.
- Eye contact : Flush with water for at least 15 minutes while holding eye lids apart. Get medical attention immediately.
- Skin contact : Clean area of contact thoroughly using soap and water. If irritation, rash or other disorders develop, get medical attention immediately.
- Ingestion : Do not induce vomiting unless advised by a physician. Call nearest Poison Control Center or Physician immediately.

SECTION 5 - FIRE FIGHTING MEASURES

- Flash point : 130 °F, 54 °C
- Method : Setaflash Closed Cup
- Lower explosion limit : 1.00 %(V) Solvent
- Upper explosion limit : 7 %(V) Solvent
- Autoignition temperature : Not available.
- Extinguishing media : If water fog is ineffective, use carbon dioxide, dry chemical or foam.
- Hazardous combustion products : Smoke, fumes. Carbon monoxide and carbon dioxide can form. Nitrogen oxides can form.
- Protective equipment for firefighters : Use accepted fire fighting techniques. Wear full firefighting protective clothing, including self-contained breathing apparatus (SCBA). Water may be used to cool containers to minimize pressure build-up.



TREMPROOF 250 GC-R 5 GAL PAIL

Version 1

Print Date 11/30/2005

REVISION DATE: 05/06/2005

Fire and explosion conditions : Vapor concentrations in enclosed areas may ignite explosively. Product may ignite if heated in excess of its flash point. Vapors may travel to sources of ignition and flashback. Closed container, may burst when exposed to extreme heat. Empty containers may contain ignitable vapors.

SECTION 6 - ACCIDENTAL RELEASE MEASURES

Use appropriate protective equipment. Avoid contact with material. Remove sources of ignition immediately. Stop flow of material if safe to do so. Contain spill and keep out of water courses. Ventilate area.

SECTION 7 - HANDLING AND STORAGE

Prevent inhalation of vapor, ingestion, and contact with skin eyes and clothing. Keep container closed when not in use. Precautions also apply to emptied containers. To prevent generation of static discharges, use bonding/grounding connection when pouring liquid. Extinguish all ignition sources including pilot lights, non-explosion proof motors and electrical equipment until vapors dissipate. Personal protective equipment must be worn during maintenance or repair of contaminated mixer, reactor, or other equipment. Keep container closed when not in use. Vapor may migrate to sources of ignition. Do not smoke, weld, generate sparks, or use flame near container.

SECTION 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Personal protection equipment

- Respiratory protection : Wear appropriate, properly fitted NIOSH/MSHA approved organic vapor or supplied air respirator when airborne contaminant level(s) are expected to exceed exposure limits indicated on the MSDS. Follow manufacturer's directions for respirator use.
- Hand protection : Use suitable impervious nitrile or neoprene gloves and protective apparel to reduce exposure.
- Eye protection : Wear appropriate eye protection. Wear chemical safety goggles and/or face shield to prevent eye contact. Do not wear contact lenses. Do not touch eyes with contaminated body parts or materials. Have eye washing facilities readily available.
- Protective measures : Use professional judgment in the selection, care, and use. Inspect and replace equipment at regular intervals.
- Engineering measures : Use only in well ventilated areas. Provide maximum ventilation in enclosed areas. Use local exhaust when the general ventilation is inadequate.

Exposure Limits

Chemical Name	CAS Number	Regulation	Limit	Form
Calcium carbonate	471-34-1	ACGIH TWA:	10 mg/m3	
		OSHA PEL:	5 mg/m3	Respirable fraction.
		OSHA PEL:	15 mg/m3	Total dust.
		OSHA TWA:	15 mg/m3	Total dust.
		OSHA TWA:	5 mg/m3	Respirable fraction.
Stoddard solvent	8052-41-3	ACGIH TWA:	100 ppm	
		OSHA PEL:	2,900 mg/m3	

TREMPROOF 250 GC-R 5 GAL PAIL

Version 1

Print Date 11/30/2005

REVISION DATE: 05/06/2005

<u>Chemical Name</u>	<u>CAS Number</u>	<u>Regulation</u>	<u>Limit</u>	<u>Form</u>
Carbon Black	1333-86-4	ACGIH TWA: OSHA PEL: OSHA TWA: OSHA TWA:	3.5 mg/m3 3.5 mg/m3 15 mg/m3 5 mg/m3	Total dust. Respirable fraction.
Talc	14807-96-6	ACGIH TWA: OSHA TWA: OSHA TWA: OSHA PEL: OSHA PEL:	2 mg/m3 0.1 mg/m3 0.3 mg/m3 15 mg/m3 5 mg/m3	Respirable fraction. Respirable. Total dust. Total dust. Respirable fraction.
Xylene	1330-20-7	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 150 ppm 435 mg/m3	
Ethylbenzene	100-41-4	ACGIH TWA: ACGIH STEL: OSHA PEL:	100 ppm 125 ppm 435 mg/m3	

SECTION 9 - PHYSICAL AND CHEMICAL PROPERTIES

Form	: Liquid
Color	: Black
Odor	: Aromatic Solvent
pH	: Not available.
Vapour pressure	: Not available.
Vapor density	: Heavier than air
Melting point/range	: Not available.
Freezing point	: Not available.
Boiling point/range	: Not available.
Water solubility	: Negligible
Specific Gravity	: 1.22
% Volatile Weight	: 11 %

SECTION 10 - REACTIVITY / STABILITY

Substances to avoid	: Oxidizing agents.Epoxies.Isocyanates.Acids.
Stability	: Stable under normal conditions. Avoid welding arcs, flames or other high temperature sources.
Hazardous polymerization	: Will not occur.

SECTION 11 - TOXICOLOGICAL INFORMATION

Calcium carbonate, CAS-No.: 471-34-1

TREMPROOF 250 GC-R 5 GAL PAIL

Version 1

Print Date 11/30/2005

REVISION DATE: 05/06/2005

Acute oral toxicity (LD-50 oral)	6,450 mg/kg (Rat)
Xylene, CAS-No.: 1330-20-7	
Acute oral toxicity (LD-50 oral)	3,523 - 8,600 mg/kg (Rat)
Acute inhalation toxicity (LC-50)	6,350 mg/l (Rat)
Ethylbenzene, CAS-No.: 100-41-4	
Acute oral toxicity (LD-50 oral)	3,500 mg/kg (Rat)
Acute dermal toxicity (LD-50 dermal)	17,800 mg/kg (Rabbit)

SECTION 12 - ECOLOGICAL INFORMATION

No Data Available

SECTION 13 - DISPOSAL CONSIDERATIONS

RCRA Class : D001: Reportable Quantity = 100 lbs. (Characteristic of ignitability)
 This classification applies only to the material as it was originally produced.
 Disposal Method : Subject to hazardous waste treatment, storage, and disposal requirements under RCRA. Recycle or incinerate waste at EPA approved facility or dispose of in compliance with federal, state and local regulations.

SECTION 14 - TRANSPORTATION / SHIPPING DATA

Not available.

SECTION 15 - REGULATORY INFORMATION
North American Inventories:

All components are listed or exempt from the TSCA inventory.

This product or its components are listed on, or exempt from the Canadian Domestic Substances List.

U.S. Federal Regulations:

SARA 313 Components	:	Anthracene	120-12-7
		Xylene	1330-20-7
		Ethylbenzene	100-41-4

SARA 311/312 Hazards	:	Acute Health Hazard
		Fire Hazard

OSHA Status: Considered hazardous based on the following criteria:	:	Irritant
--	---	----------

OSHA Flammability	:	II
-------------------	---	----

Regulatory VOC (less water and exempt solvent)	:	144 g/l
VOC Method 310	:	11 %

Chemical is listed as an IARC, NTP, OSHA, or ACGIH Carcinogen:

TREMPROOF 250 GC-R 5 GAL PAIL

Version 1

Print Date 11/30/2005

REVISION DATE: 05/06/2005

Carbon Black 1333-86-4

U.S. State Regulations:

MASS RTK Components : Calcium carbonate 471-34-1
 Stoddard solvent 8052-41-3
 Carbon Black 1333-86-4
 Talc 14807-96-6
 Anthracene 120-12-7
 Xylene 1330-20-7

Penn RTK Components : Aromatic process oil 64742-90-1
 Polyurethane Polymer NJ TSRN# 51721300-5358P
 Calcium carbonate 471-34-1
 Stoddard solvent 8052-41-3
 Polyvinyl chloride 9002-86-2
 Carbon Black 1333-86-4
 1,2-Benzenedicarboxylic acid 68515-45-7
 1,2-Benzenedicarboxylic acid 111381-89-6
 1,2-Benzenedicarboxylic acid 68515-44-6
 Talc 14807-96-6
 Anthracene 120-12-7
 Xylene 1330-20-7

NJ RTK Components : Aromatic process oil 64742-90-1
 Polyurethane Polymer NJ TSRN# 51721300-5358P
 Calcium carbonate 471-34-1
 Stoddard solvent 8052-41-3
 Polyvinyl chloride 9002-86-2
 Carbon Black 1333-86-4
 Xylene 1330-20-7

Chemicals known to the State of California to cause cancer birth defects and/or other reproductive harm:

1333-86-4 Carbon Black
 100-41-4 Ethylbenzene
 117-81-7 Dioctyl phthalate
 108-88-3 Toluene
 14808-60-7 Crystalline Silica (Quartz)/ Silica Sand

Canadian Regulations:

WHMIS Classification : B3, D2A

This is a "controlled product" under the Canadian Workplace Hazardous Materials Information System (WHMIS).

SECTION 16 - OTHER INFORMATION

HMIS Rating :

Health	2
Flammability	2
Reactivity	1
PPE	

0 = Minimum
 1 = Slight
 2 = Moderate
 3 = Serious
 4 = Severe



TREMPROOF 250 GC-R 5 GAL PAIL

Version 1

Print Date 11/30/2005

REVISION DATE: 05/06/2005

Further information:

For Industrial Use Only. Keep out of Reach of Children. The hazard information herein is offered solely for the consideration of the user, subject to their own investigation of compliance with applicable regulations, including the safe use of the product under every foreseeable condition.

Prepared by: Rich Mikol

Legend

ACGIH - American Conference of Governmental Hygienists
CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act
DOT - Department of Transportation
DSL - Domestic Substance List
EPA - Environmental Protection Agency
HMIS - Hazardous Materials Information System
IARC - International Agency for Research on Cancer
MSHA - Mine Safety Health Administration
NDSL - Non-Domestic Substance List
NIOSH - National Institute for Occupational Safety and Health
NTP - National Toxicology Program
OSHA - Occupational Safety and Health Administration

PEL - Permissible Exposure Limit
RCRA - Resource Conservation and Recovery Act
RTK - Right To Know
SARA - Superfund Amendments and Reauthorization Act
STEL - Short Term Exposure Limit
TLV - Threshold Limit Value
TSCA - Toxic Substances Control Act
TWA - Time Weighted Average
V - Volume
VOC - Volatile Organic Compound
WHMIS - Workplace Hazardous Materials Information System